

Water Level Indicators



Features:

- An economical and reliable means of obtaining accurate water level data in water wells
- Contact of the electrode assembly with the water surface is indicated by an LED and the sound of the audio alert beeper
- Brass socket assembly is 3/8" in diameter and can be replaced in the field
- Cable is two-conductor, steel and copper plated, with a tensile strength of 300 pounds and a tough plastic insulating jacket
- Mounted on a small handheld spool and stand which can be used conveniently to let out or withdraw the cable and electrode assembly
- Standard lengths: 100, 200, 300, 400, and 500 feet; 50, 100, 150 meters
- Depth indication is provided by numbered metal tags securely crimped to the cable at intervals of five feet or every meter on metric models
- Self-contained power supply using a standard 9V battery

Model	Description	Price
WLT-100	Water Level Indicator, 100 ft.	\$562
WLT-200	Water Level Indicator, 200 ft.	\$628
WLT-300	Water Level Indicator, 300 ft.	\$694
WLT-400	Water Level Indicator, 400 ft.	\$786
WLT-500	Water Level Indicator, 500 ft.	\$826
WLTM-50	Water Level Indicator, 50m	\$619
WLTM-100	Water Level Indicator, 100m	\$745
WLTM-150	Water Level Indicator, 150m	\$868

Water Depth Gauge



Features:

- Pocket-sized depth sounder
- Reads in feet or meters, to the nearest tenth, through a solid hull, inflatable bottom, or black ice
- Reads from 2 to 260 feet
- Each reading is backlit and stays displayed for 10 seconds
- Simply put the head in the water or against the hull of a boat
- 400 kHz with 6° beam angle
- Extremely accurate

Specifications:

Range:	2 to 260 ft or 0.6 to 79 m
Frequency:	400 kHz
Waterproof:	To 160 ft or 50 m
Power Supply:	Standard 9V dry cell battery
Battery Life:	500 10-second readings
Dimensions:	7.7 x 1.7" (198 x 42 mm)
Weight:	10 oz (300 g)

Model	Description	Price
SM-5	Water Depth Sounder	\$238