



FLIR G306™

Industry-Leading Optical Gas Imaging (OGI)
Camera for Sulfur Hexafluoride (SF₆)



The FLIR G306 is an innovative Optical Gas Imaging (OGI) camera used to detect sulfur hexafluoride (SF₆), ammonia (NH₃), ethylene (C₂H₄), and other industrial gas leaks. Designed with your safety and efficiency in mind, this advanced cooled thermal camera can detect dangerous and environmentally harmful gases from safe distances. Reduce inspection time by scanning large areas without interfering with electric utility delivery or shutting down industrial operations. Featuring a rotating, color LCD touch screen, the G306 is ideal for detecting gas in complex systems including electric utility transmission facilities and industrial plants. Combined with FLIR Ignite™ software, the FLIR G306 allows you to easily upload images and videos to the cloud where you can edit, organize, store, and share data.



SUPERIOR GAS VISUALIZATION

Detect gas leaks accurately in real-time

- Efficiently scan thousands of components with FLIR's patented High-Sensitivity Mode (HSM)
- Measure temperatures from -40°C to 500°C (-40°F to 932°F)
- Auto-adjust the level and span of your image with 1-Touch Level/Span
- Comfortably inspect facilities with superior ergonomics

IMPROVED SOFTWARE INTEGRATION

Record and report findings efficiently with the FLIR ecosystem

- Effortlessly edit and store images in the cloud, and wirelessly transfer files using the included FLIR Ignite cloud service
- Easily incorporate with third-party software solutions
- Built in Wi-Fi and Bluetooth® allow you to connect to smartphones or tablets
- Conveniently navigate large areas with FLIR Inspection Route and GPS log on board

BETTER ERGONOMICS FOR OPERATION

Comfortably interact with the camera

- Expand inspection capabilities with quick and easy exchangeable lens options
- View targets from any direction with rotating 10.16 cm (4 in) LCD touch screen
- Efficiently operate with improved touch screen Graphical User Interface (GUI)
- Advanced features to streamline the inspection process, including Multi-REC (recording mode)

SPECIFICATIONS

Detector and Optics Data		Communication & Data Storage	
FLIR G306		FLIR Inspection Route	Enabled in the camera
IR Resolution	320 × 240 pixels	MultiREC Recording	Record multiple files automatically in customizable order
Thermal Sensitivity/NETD	15 mK at 30°C (86°F)	GPS	Location data automatically added to every still image; first frame in video from built-in GPS; data logging feature
Detector Type	Focal plane array (FPA), cooled QWIP	Compass	Yes
Spectral Range	10.3 μm to 10.7 μm	Cloud Services (via Wi-Fi)	FLIR Ignite for direct, secure image uploading, organizing, storage, and sharing (required firmware available)
Detector Pitch	30 μm	Storage Media	Removable SD card
Sensor Cooling	Stirling Microcooler (FLIR MC-3)	Image File Formats	Standard JPEG, measurement data included. Infrared-only mode.
Gas Sensitivity	SF ₆ : <0.3 ppm x m (ΔT = 10°C, Distance = 1 m)	Communication Interfaces	USB 2.0, Bluetooth via headset, Wi-Fi, HDMI
Digital Image Enhancement	High sensitivity mode (HSM), noise reduction filter	Video Out	HDMI; DVI
Available Lenses	24° × 18° (23 mm); 14.5° × 10.8° (38 mm); 6° × 4.5° (92 mm)	Video Recording and Streaming	
F-Number	1.59	Radiometric IR Video Recording	RTRR (.csq)
Focus	Autofocus, Manual focus	Non-Radiometric IR or Visual Video	H.264 to memory card
Image Presentation		Radiometric IR Video Streaming	Over UVC
Display	4", 640 × 480 pixel rotatable, touchscreen LCD	Non-Radiometric IR Video Streaming	H.264 (AVC) or MPEG4 over RTSP (Wi-Fi); MJPEG over UVC and RTSP (Wi-Fi)
Viewfinder	Built-in, tiltable OLED, 800 × 480 pixels	Visual Recording	H.264 to memory card
Image Presentation Modes	IR image, visual image, high sensitivity mode (HSM)	Environmental & Certifications	
Color Palettes	Arctic, White hot, Black hot, Iron, Lava, Rainbow, Rainbow HC	Operating Temperature Range	-20°C to 50°C (-4°F to 122°F)
Zoom	1–8× continuous, digital zoom	Storage Temperature Range	-30°C to 60°C (-22°F to 140°F)
Laser Pointer	Class 2	Encapsulation	IP54 (IEC 60529)
Measurement & Analysis		Shock	25 g (IEC 60068-2-27)
Measurement Temperature Range	-40°C to 500°C (-40°F to 932°F)	Vibration	2 g (IEC 60068-2-6)
Accuracy	±1°C (±1.8°F) for temperature range (0°C, to 100°C, 32°F to 212°F) or ±2% of reading for temperature range (>100°C, >212°F)	Additional Information	
Image Analysis	10 spots, 5 boxes with max/min/average, 1 line (horizontal or vertical), measurement corrections	Battery Type	Rechargeable Li-ion battery; 7.4 V, charged in camera or separate 2-bay charger
Annotations		Battery Operating Time	>2.5 hours at 25°C (68°F) and typical use
Voice	60 seconds with Bluetooth on still images and video	Battery Charging Time	2.5 hours to 95% capacity, charging status indicated by LEDs
Text	Text from predefined list or soft keyboard on touchscreen	Camera Size	251.6 mm × 164.5 mm × 170.9 mm (9.9 in × 6.48 in × 6.73 in)
Image Sketch	Yes: on infrared only	Camera Weight	3 kg (6.18 lb)
		Mounting Interfaces	UNC ¼"-20
		Box Contents	
		Packaging	Infrared camera with lens, battery: 2 pcs., battery charger, power supply including multi-plugs, hand strap, neck strap, lens cap, lens cap strap, memory card, HDMI-HDMI cable, USB cable, screwdriver TX20, printed documentation, and hard transport case

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

©2022 Teledyne FLIR, LLC. All rights reserved.

Revised 03/01/23
G306_Datasheet-LTR 21-0000



1.800.561.8187

www.itm.com

information@itm.com