

4-VALVE ALUMINUM MANIFOLD

Product Specifications

Item Numbers/Product Descriptions					
Refrigerants	With 60" Hoses and Ball Valve Adapters	Without Hoses	Temp.	Pressure Range Low	Pressure Range High
R410A	1839109 4V410H	1839111 4V410	F/C	-30" HG/300/ 500 psi	0/800 psi
HP22-407C-410A (Heat Pump)	1839128 4V22407410H	1839129 4V22407410		0/800 psi	0/800 psi
R22-404A-410A	1839130 4V22404410H	1839132 4V22404410	F	-30" HG/300/ 500 psi	0/800 psi
Accuracy		Class 1 - 1% Accuracy (full scale)			
Gauge Connection Type		1/8" NPT Male Fitting			
Valve Type		Double O-ring Piston Style			
Valve Seat (Orifice)		Replaceable Stainless Steel (SAE-style straight thread with O-ring)			
Sight Glass		Bonded steel with SAE-style straight thread with O-ring			
Vacuum Port		3/8" full bore (quantity 1)			
Charge Ports		1/4" (quantity 3)			
Hoses Included		1839143 H60BVS4 60" Hoses with Ball Valve Adapters - Set of 4			
Dimensions					
Length	8-7/8"	8-7/8"			
Width	4"	4"			
Height	7-1/8"	7-1/8"			
	without hook	without hook			
Weight	7.1 lbs.	3.4 lbs.			