




Band Size	Circumference	
	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

Item	Band Size	Coil Cord
2225	Small	Not Included
2226	Medium	Not Included
2227	Large	Not Included
2228	Small	6' (2234)
2229	Medium	6' (2234)
2230	Large	6' (2234)
2231	Small	12' (2235)
2232	Medium	12' (2235)
2233	Large	12' (2235)

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a [SCS MagSnap™ 360 Coil Cord](#) (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

U.S. Patent Pending

MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND

SCS

1.800.561.8187

www.itm.com

information@itm.com

DRAWING
NUMBER
2225

DATE
August
2015