


OBS 2VU SERIES

2 Sided Pressure Gauge



- ✓ All Plastic One Piece Design
- ✓ No Filling or Assembly Required
- ✓ Completely Corrosion Resistant



Cutting-Edge One-Piece Plastic Pressure Gauges for Corrosive Environments

The OBS 2VU Series is the industry's only integral molded one-piece plastic pressure gauge and gauge guard. Gauge guards are utilized to protect the pressure gauge from any corrosive media in the process system via an isolator.

The OBS 2VU Pressure Gauges are a one-piece design and come factory pre-filled, resulting in an industry leading accuracy of $\pm 1.5\%$. Eliminating the need for filling saves the user time and the difficulty of having to fill a gauge isolator.

The 3 movable red, yellow and green range tabs are designed to act as a visual pressure alert for bag or filter change-outs.

The OBS 2VU Series is available in PVC, PP & PVDF all equipped with a Teflon® Diaphragm, making the entire unit completely corrosion resistant and the perfect pressure gauge for chemical applications.

Engineering the entire body in a plastic housing rather than just the gauge guard allows users to be confident that the complete unit will stand up in even the most corrosive environments.

Features

- ✓ Industry's Highest Accuracy | $\pm 1.5\%$
- ✓ PVC | PP | PVDF
- ✓ Teflon® Bonded Diaphragm
- ✓ Large 2 ½" Dial
- ✓ All Plastic
- ✓ Dual Scale | psi | bar

Integral Molded Gauge | Gauge Guard

- ✓ No Filling or Assembly Required
- ✓ Increased Accuracy Compared to 2 Piece Gauge + Gauge Guard
- ✓ Convuluted Teflon® Diaphragm for Higher Sensitivity



Pressure Range Markers

- ✓ Notification for Filter | Strainer Change Out
- ✓ Easily Customizable to your Process Conditions
- ✓ Eliminates Manual Marking on Gauge
- ✓ Red | Yellow | Green - Markers



Factory Pre-Filled

- ✓ Reduces Installation Time
- ✓ Highest Accuracy
- ✓ Eliminates the Mess of Self Filling
- ✓ Removes Air Bubble Issues



PVC

PP

PVDF

RoHS
Compliant

CE

OBS 2VU SERIES

2 Sided Pressure Gauge




Specifications

Mounting	Direct Mount Bottom Connection
Process Connection	½" MNPT FNPT G Threaded Flanged
Measuring Principle	Bourdon Tube 316SS
Pressure Ranges psi	0-15 0-30 0-60 0-100 0-160 0-200
Lens	High Impact Polycarbonate
Filling	Glycerin Silicon* Halocarbon*
Accuracy	± 1.5%
Operating Temperature	PVC - 140°F PP - 190°F PVDF - 240°F
Dial Diameter	2 ½" Double Sided

Installation Instructions

- Do not tighten by grasping the case of the gauge as this may cause damage. Always pressure test connections for leaks with water prior to use on chemical service.
- Before installing the 2VU series pressure gauge, ensure attention is given to the process liquid, chemical compatibility, temperature, vibration, pressure spikes and other climatic and application conditions that may adversely affect the performance.
- The user shall ensure that the correct gauge pressure range and the correct materials of construction are selected.



Temperature | Pressure Graphs | Non Wetted

Note: The Pressure/Temperature graphs are specifically for the Truflo® Pressure Gauges. During system design the specifications of all components must be considered.

■ = PVC ■ = PP ■ = PVDF

Model Selection

2VU - P - 0-30 - M

Body Material	Pressure Range Psi	Connection
P - PVC	0 - 15 0 - 100	F - 1/2" FNPT
PP - PP	0 - 30 0 - 160	M - 1/2" MNPT
PF - PVDF	0 - 60 0 - 200	G - G Thread
		F - Flanged

