

FC Series Surface Thermometers

- Dual magnet mount surface thermometers specifically designed to be used on horizontal ferrous non-horizontal surfaces
- Features two alnico magnets that act as the thermometer's base and hold it in place on ferrous surfaces
- Bimetallic sensor is a specially processed alloy that is preconditioned and pre-tested for permanent calibration and maximum stability
- Sensor is located in a draft shield and is in virtual thermal contact with the surface to be measured which means a relatively quick response time
- Reaches sensing equilibrium (stability) within three minutes
- Designed for applications such as: hot plates; griddles; die-cast dies; foundry core boxes; annealing ovens; weld preheats; motors; generators; engines; bearings; boilers, tanks, and drums



Temperature Range: 312FC: 0 to 250°F (-20 to 120°C);
314FC: 50 to 750°F (10 to 400°C)

Resolution: 312FC: 2°F/1°C;
314FC: 10°F/5°C

Accuracy: ±2% of full scale

Time Constant: From 0.06 to 1 min.
(depending on range)

Dimensions: 2" dia. x 1/2 h. (5.1 x 1.3 cm)

Weight: 1-1/2 oz (43 g)

Model	Description
312FC	Magnetic Surface Thermometer
312FC-NIST	Surface Thermometer & NIST
314FC	Magnetic Surface Thermometer
314FC-NIST	Surface Thermometer & NIST
CERTITM1	NIST Calibration Certificate



GlobalTestSupply.com/Baker



ITM.com/Baker