

Type 196 / 96 M / 196 LED - Specifications

Туре		196		96 M		196 LED
Accuracy - top read	00	1/32" @ 72"	0	1/32" @ 72"	0 =	1/32"@ 72"
Accuracy - bottom read	7	1/32" @ 72"	-	1/32" @ 72"	-	1/32"@ 72"
Vial type		1 x horizontal		1 x horizontal	-	1 x horizontal
	0	2 x vertical		2 x vertical	-	2 x vertical
End caps		Anti-slip / Shock		Anti-slip / Shock absorbing / Removable		Anti-slip / Shock absorbing / Removable
<u> </u>		absorbing / Removable				
Special feature	- [[{ }]]	-		Rare-earth magnets		2 LED Lights
	18 31				THE R.	
Length	- 13 - 81	Part No.		Part No.		Part No.
16"	R S	37416		38616	6	-
24"	T.	37424	446	38624	210	39324
32"	STABILA	37432	TAB	38632	STABILA	-
36"	TE I	37436	STABILA S	38636		-
48"		37448	100	38648	-	39340
58"		37459		-		-
48" & 16" Set	18 8	37816		-	15 31	-
58" * & 32" Set	- 13 - 11	37832		-	I 31	-
72" *	B 8	37472		38672	18 31	-
78" *	M	37478		38678		-
78" & 32" Set	-	37532 Jamber® Set		38532 Mag. Jamber® Set	u	-
96" *		37496	-000	38696	and the same of	-
			(===)			
			177		1000	
	- 46		- 18			
	All Property lies					

^{*} Levels \geq 58" have a continuous bridge over the horizontal vial.



