

Specifications



	nanoReel N85S	microDrain D30/D65S	microReel L100/L100C
Camera Head	0.62" (15.5mm)	0.86" (22mm)	0.98" (25mm)
Cable Length	85' (25m)	30' (10m) / 65' (20m)	100' (30m)
Cable Diameter	0.25" (6.3mm)	0.33" (8.3mm) flexible	0.27" (6.7mm) stiff
Line Capacity	1" to 2" (19 - 50mm)	1" to 3" (25 - 76mm)	1.5" to 4" (38 - 100mm)
Weight	9.5 lbs. (4.1 kg)	8.6 lbs. (3.9 kg) / 9.8 lbs. (4.4 kg)	10.3 lbs. (4.7 kg)
Length	13.25" (33.7 cm)	13.25" (33.7 cm)	13.25" (33.7 cm)
Width	6.6" (16.8 cm)	6.6" (16.8 cm)	6.6" (16.8 cm)
Height	17.5" (44.5 cm)	17.5" (44.5 cm)	17.5" (44.5 cm)
Resolution	510 x 496 NTSC	510 x 496 NTSC	510 x 496 NTSC
Ball Guide	2 included	2 included	2 included
Sonde	512Hz	Optional 512Hz	512Hz
Counter	NA	NA	Optional
Applications	Boiler Tube Inspection Supply Line Inspection Sprinkler Plumbing Inspection Small Diameter Drains	Pools (1.5" pressure 90s) Toilet Traps Sink Traps Small Diameter Drains	Sewer Laterals Chimneys Floor Drains General Drain Inspection
Reel Only (SeeSnake CCU)	Cat. No. 40008	Cat. No. 32663/37468	Cat. No. 35133/35183
Reel Only (micro CA-300)	Cat. No. 39998	Cat. No. 33103/37473	Cat. No. 35143/35188
System (w/micro CA-300)	Cat. No. 40818	Cat. No. 40778/40788	Cat. No. 40798/40808
Removable Drum Only	Cat. No. 40443	Cat. No. 35113/37483	Cat. No. 34623/35243

The nanoReel Inspection Camera Is Compatible With The Following CCUs



MINIPak Monitor
Catalog No. 32748



DVD Pak 2 Monitor
Catalog No. 33198



LCD Pak Monitor
Catalog No. 37843



All Larger SeeSnake® CCUs



micro CA-300 Inspection Camera
Catalog No. 37888

Catalog No.	Description	Weight		Std Pack
		lbs.	kg	
37843	LCD Pak Monitor w/2 Batteries and Charger (115V)	22.2	10	1
33203	DVD Pak Monitor w/Battery and Charger – OLED (115V)	11.5	5.2	1
33198	DVD Pak Monitor w/Battery and Charger – LCD (115V)	11.5	5.2	1
32748	MINIPak Monitor w/Battery and Charger (115V)	7.9	3.6	1
37888	micro CA-300 Digital Inspection Camera	1.93	0.83	1
30198	Replacement Battery for micro CA-300 Camera	.24	.11	1
30073	Audio Recorder for micro CA-300 Camera	.25	.12	1