
### **Bilingual Lockout Tags**

- Spanish/English tags provide extra safety and information in bilingual situations
- · High-visibility lettering





 Write-on tag with 7/8 in. grommet can be padlocked to device to help prevent unauthorized removal

Description	Quantity	Part No.
Bilingual Lockout Tags - Do Not Operate (striped)	5	44-841

#### Flash Protection Labels and Signs







44-893

44-8

44-896

National Electric Code 110.16 Flash Protection: Switchboards, panel boards, industrial control panels and motor control centers, in other than dwelling occupancies, that are likely to require examination, adjustment, servicing or maintenance while energized, shall be field marked to warn qualified persons of potential electric arc flash hazards. The marking shall be located so as to be clearly visible to qualified persons before examination, adjustment, servicing or maintenance of the equipment.

Description	Туре	Size	Qty.	Part No.
NEC Arc Flash, Warning	Self- Sticking Polyester	3-1/2 in. x 5 in.	5	44-892
NEC Arc Flash, Warning			100	44-892BK
NEC Arc Flash, Warning		5 in. x 7 in.	5	44-893
NEC Arc Flash, Warning			5	44-894
NEC Arc Flash, Danger		4 in. x 6 in.	5	44-895
NEC Arc Flash, Warning		7 in. x 10 in.	1	44-896

# **Lockout Signs**







 Resistant to both chemicals and abrasion protected graphics for indoor and outdoor use

Legend	Material	Size (In.)	Part No.
Lockout Sign - OSHA Regulation, 36 in. clearance	Self-sticking	3-1/2 x 10	44-877
Lockout Sign - OSHA Regulation (Bilingual) 36 in. clearance	polyester	7 x 10	44-878
Lockout Sign - Danger- Breakers Locked Out	Magnetic	5 x 7	44-890

### Safety Signs

 Resistant to both chemicals & abrasion – protected graphics for indoor & outdoor use



	Legend	Material	Size (In.)	Part No.
	C ( , C' )	Fiberglass	10 x 14	44-862
	Safety Sign – Danger- High Voltage	Self-Sticking Polyester	7 x 10	44-863
	Safety Sign – Danger- High Voltage-Keep Out	Fiberglass	10 x 14	44-880
		Self-Sticking Polyester	7 x 10	44-881
	Safety Sign - Danger- High Voltage-Spanish	Self-Sticking Polyester	7 x 10	44-865

## Voltage & Conduit Markers

44-289

44-299







44-410

- Identify junction boxes, switches, circuit breakers, raceways, pipe and fuse boxes
- Non-conductive for user safety
- · High-adhesion properties with easy removal
- Resist abrasion, moisture, dirt and oil
- Non-smear, black legend on bright orange background for high visibility
- Specifications: Temperature Range: -40°F to 180°F (-40°C to 82°C)

Adhesion: 45 oz./in. width ultimate

Description	Large Part No. (2-1/4 in. x 9 in.) 1/card	Medium Part No. (1-1/8 in. x 4-1/2 in.) 4/card	Small Part No. (2-1/4 in. x 1/2 in.) 18/card
120/208V	44-295	44-296	_
277/480V	44-298	44-299	_
120V	_	44-353	-
208V	_	44-355	-
240V	_	44-358	-
277V	-	-	44-410
480V	44-314	44-364	-
Danger	44-289	_	_
High Voltage	44-292	-	-