



# Pipe Surface Thermometer


## Clip-On



- Accuracy  $\pm 2\%$  of Full Scale
- 6 Temperature Ranges
- Lexan Lens Cover Available
- A2LA/NIST Certification Available
- Monitor Hot or Cold Pipelines
- Each Instrument is Individually Calibrated
- For Pipe O.D.  $3/4"$  to  $2\ 3/8"$
- 3 Clip Sizes Snap Instantly in Place



**ISO 17025**  
ACCREDITED  
LABORATORY



Calibrated and designed for pipe-surface temperature measurement, these thermometers can be used on pipes up to  $2\ 3/8"$  diameter. For larger pipes, see reverse side of this sheet.

Ease of use and low cost make these instruments indispensable for monitoring pipes.

### SPECIFICATIONS

Time Constant	42 Seconds
Accuracy	$\pm 2\%$ of full scale range
Height	1 in. (2.5 cm)
Diameter	2 in. (5.1 cm)
Weight	1 oz. (28 g)
Shipping Weight	1 lb. (454 g)

Range	° Division	Small Clip $3/4"$ to $7/8"$	Medium $1"$ to $1\ 5/8"$	Large $1\ 5/8"$ to $2\ 3/8"$
$0^{\circ}$ to $150^{\circ}\text{F}$	$2^{\circ}$	483FS	483FM	483FL
$-50^{\circ}$ to $250^{\circ}\text{F}$	$2^{\circ}$	484FS	484FM	484FL
$70^{\circ}$ to $370^{\circ}\text{F}$	$2^{\circ}$	485FS	485FM	485FL
$-20^{\circ}$ to $70^{\circ}\text{C}$	$2^{\circ}$	483CS	483CM	483CL
$-40^{\circ}$ to $120^{\circ}\text{C}$	$2^{\circ}$	484CS	484CM	484CL
$20^{\circ}$ to $180^{\circ}\text{C}$	$2^{\circ}$	485CS	485CM	485CL