

# 120V AC CIRCUIT BREAKER FINDER

W/FLASHLIGHT, NCVT & GFCI RECEPTACLE TESTER

- cULus Certified (UL 1436, CSA C22.2 No. 160), CAT II 150V
- Quickly and easily identifies circuit breakers/fuses without disrupting power on energized 120V AC circuits
- Clear Visual and Audible indicators (Audible can be muted)
- NCVT in receiver tip indicates presence of AC voltage between 80-300V AC
- Flashlight in receiver operates independently of the tester functions and can be used to illuminate work area
- Transmitter tests outlet wiring configurations (indicated via Green/Red LEDs) and tests GFCIs
- Receiver powers off automatically after 5 minutes of non-use to conserve battery life



**Narrower Tip**  
improves breaker  
identification accuracy

**LED Flashlight**  
operates independently  
and illuminates work area

**Transmitter**  
sends a signal over the conductors when  
connected to an energized circuit. It also  
identifies the presence of power and  
indicates correct/incorrect wiring con-  
ditions via illuminated Green and Red  
LED's. A GFCI test light illuminates  
when the GFCI Test button is pressed,  
indicating the activation of the GFCI  
test. The GFCIs will trip if they are  
functioning properly



NOTE: Receptacle MUST be properly  
grounded for the GFCI test to  
work properly.

NOTE: The transmitter works on  
LIVE/Energized circuits only


**Receiver**  
powers off automatically after  
five minutes of non-use to  
conserve battery life

**Lanyard Mount**

**NCVT**  
in receiver tip indicates presence  
of AC voltage between 80-300 volts  
(visual flashing red LEDs  
& audible indicators)



**Receiver**  
reads the transmitter's signal  
and identifies the breaker/  
finder energizing the circuit  
by illuminating a flashing  
green LED and emitting  
beeps once it determines  
the breaker/fuse  
with the strongest signal.




**LED  
Flashlight**

**Audible Defeat**  
for noise  
sensitive areas

**On/Off** toggles  
between circuit breaker  
finding and NCVT functions  
(default circuit breaker  
finding)

**61-535**  
120V AC Circuit Breaker Finder  
w/Flashlight, NCVT & GFCI  
CAT II 150V | cULus Listed



**TL-532A**  
Test Lead & Adapter KIT (sold separately)



**SCAN**  
to learn more

THE ELECTRICIAN'S  
**CHAMPION** **IDEAL**

www.itm.com

information@itm.com

1.800.561.8187

# 120V AC CIRCUIT BREAKER FINDER

W/FLASHLIGHT, NCVT & GFCI RECEPTACLE TESTER

**NEW**



**SCAN**  
to learn more



**61-535**  
Receiver

**61-535**  
Transmitter



## CIRCUIT BREAKER FINDER SELECTION GUIDE



**REPLACED BY THE ENHANCED  
AND ERGONOMIC 61-535**



		REPLACED BY THE ENHANCED AND ERGONOMIC 61-535	
CIRCUIT BREAKER FINDER SELECTION GUIDE			
TRANSMITTER FEATURES	61-535	61-534	61-532
CAT Rating (Safety)	CAT II 150V	CAT II 300V	CAT II 300V
Listing	UL 1436, CSA C22.2 No. 160	UL 1436, CSA C22.2 No. 160	UL 1436, CSA C22.2 No. 160
Line Voltage	Line Powered (120V AC)	Line Powered (120V AC)	Line Powered (120V AC)
Supply Frequency	60Hz	47-63Hz	47-63Hz
Weight	28.35g (approx.)	50g (approx.)	50g (approx.)
Flashlight	✓	—	—
NCVT	✓	—	—
Power Consumption	1.5W max. @ 120V AC	200mW max. @ 120V AC	200mW max. @ 120V AC
Correct/Wiring Fault/Polarity Indications	✓	✓	—
GFCI Trip/Test	✓	✓	—
GFCI Trip Test Indicator	✓	—	—
RECEIVER FEATURES			
Visual and Audible Indicators	✓	✓	✓
Low Battery Indication	✓	✓	✓
Auto Power Off (after no activity)	(after 5 mins.)	(after 10 mins.)	(after 10 mins.)
Battery Type	9V	9V	9V
Weight	85g (w/o battery)	85g (w/o battery)	85g (w/o battery)
Warranty	2-Year*	2-Year*	2-Year*
ACCESSORIES			
Light Socket and 3-prong to 2-prong Adapters, Alligator Clips	TL-532A	TL-532A	TL-532A

\* Visit [www.idealind.com](http://www.idealind.com) for warranty details.

Specifications are subject to change without notice.



IDEAL INDUSTRIES, INC.

IDEAL INDUSTRIES, INC.  
1800 S. Prairie Drive, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA

International offices:  
Australia • Canada • China • India • Mexico • UK

For complete sales office contact information, visit us at:

Form No. D-5070

1877

1.800.561.8187

[www.itm.com](http://www.itm.com)

[information@itm.com](mailto:information@itm.com)