



645

Dual Input Differential Manometer

Features

Differential input with ± 29 PSI range.
Seven units of measure (mbar, kPa, PSI, mmHg, inHg, mH2O, inH2O).
Display - 4 digit dual line with backlight
Smooth - Stabilizes display when measuring fluctuating pressures
Data Hold - Freezes reading on display.
Min / Max - Records Min/Max readings
Auto Off - Conserve battery power.

Specifications

Measurement Range: ± 29 psi
Display: 4 Digit Dual line LCD with backlight
Input Type: Dual Differential (compression fittings)
Resolution (max): 0.01 psi
Accuracy: $\pm (0.2\% \text{ Full scale} + 3 \text{ digits})$
Functions: One Touch Zero, Data Hold, Back-light, Unit Selection, Smoothing, Auto power Off, Min / Max Record, Resolution Selection
Units of Measure: 7 Units (mbar, kPa, PSI, mmHg, inHg, mH2O, inH2O)
Battery Type: 9V alkaline
Battery Life: 80hours (Typical)
Auto Power Off: 30 minutes

Standard Accessories (Included): 9V alkaline battery (A009A), replacement tubing (A601)



Copyright © 2008 Test Products International, Inc.

information@itm.com

www.itm.com

1.800.561.8187