

RIDGID®

K9-306 FlexShaft™ Machine

**Clears 3" to 6" (75 to 150 mm) Pipe
Up to 125' (38 m)**



Purpose-built for the professional, the NEW RIDGID® FlexShaft K9-306 quickly clears grease buildup, roots and heavy scale using 125' of 3/8" cable for 3" - 6" pipes with one step of the foot switch. It features a professional 1.5 HP internal universal motor for maximum power and longevity, a fully enclosed drum to minimize set-up and clean up time, and a telescoping handle with multiple wheels and grab points to make loading, unloading, transporting, and storage easy.

- **Wall-To-Wall Clean:** Chain knockers expand for full pipe cleaning
- **Simultaneous Camera Use:** FlexShaft machines let you keep your camera in-pipe while you work
- **Increase Productivity:** Faster setup and cleanup, quick cleaning, and easy to transport for additional time savings
- **Versatile Frame:** Utilize 2 or all 4 wheels for ease of maneuverability and transport. Telescoping handle allows for a compact footprint in tight job site locations while creating a low profile for storage

1.800.561.8187

www.itm.com

information@itm.com

RIDGID® FlexShaft machines utilize specialized chain knockers attached to a flexible cable that are spun at high speeds. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.



SPECIFICATIONS

- Model.....**K9-306**
- Drain Capacity (Nom.)3" to 6" (80 – 152 mm)
- Cable Diameter (without Sheath) $\frac{3}{8}$ " (10 mm)
- Cable Assy. Diameter (with Sheath) $\frac{5}{8}$ " (15,8 mm)
- Cable Assembly Length125' (38 m)
- Rotational Speed2000 RPM
- Dimension36.2" x 20.4" x 32.6" (919.5 mm x 518.2 mm x 828 mm) Handle Down
36.2" x 20.4" x 44.8" (919.5 mm x 518.2 mm x 1137.92 mm) Handle Up
- Operating temperature20°F - 140°F (-6°C - 60°C)

ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.)	(kg)
66593	K9-306 NA	FlexShaft, K9-306 NA 3"-6" (75 mm - 150 mm) Pipes Includes: $\frac{3}{8}$ " by 125' (10 mm x 38 m) cable and kit*	159	72.1

* K9-306 includes: 4" Chain Knocker, 6" Chain Knocker, FlexShaft Lubricant, 4MM Hex Key, 3MM Hex Key, RIDGID Tool Bag, 12" Sheath Stock, 4" Sheath Spacer, 6" Sheath Spacer, Manual Pack.

Chain Knockers

- All pipe types
- For soft blockages and grease



Carbide Tipped Chain Knockers

- Hard walled pipes
- For scale, roots, grease and soft blockages



Penetrating Head Chain Knockers

- Hard walled pipes
- For wipes, scale, roots, grease and soft blockages



ACCESSORIES

CATALOG NO.	DESCRIPTION
66618	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 3" (75 mm) pipe, 3 chain
66623	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 4" (100 mm) pipe, 3 chain
66628	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 5" - 6" (125 - 150 mm) pipe, 3 chain
66633	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 3" (75 mm) pipe, 3 chain, carbide tip
66638	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 4" (100 mm) pipe, 3 chain, carbide tip
66643	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 5" - 6" (125 - 150 mm) pipe, 3 chain, carbide tip
66648	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 3" (75 mm) pipe, 3 chain, penetrating head
66653	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm) cable, 4" (100 mm) pipe, 3 chain, penetrating head
66658	FlexShaft Knocker, $\frac{3}{8}$ " (10 mm), 5" - 6" (125 - 150 mm) pipe, 3 chain, penetrating head
64338	RIDGID FlexShaft Lubricant, 8 oz
66663	FlexShaft $\frac{3}{8}$ " (10 mm) Assembly, 125' (38 m) cable, sheath, couplings
66668	FlexShaft $\frac{3}{8}$ " (10 mm) Sheath Stock, 12" (30 cm)



All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-20-A (320) Effective Date: Feb 1, 2020
©2020 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries.