RIDGID

SeeSnake NANOreel[®] **Inspection Camera**



The RIDGID® SeeSnake® NANOreel® opens up new possibilities in drain inspection with the smallest-diameter camera and most flexible push cable of all SeeSnake® systems. Inspect a wide array of specialty applications that previously only bore scopes could reach.

- Small 15.5 mm camera head with ultra flexible push cable navigates tight spaces in 1" to 2.5" lines
- A built-in kickstand offers in-field versatility with multiple configurations
- Lightweight and compact carrying case design is easy to carry to jobsites and store in-between
- Integrated 512 Hz sonde allows for easy line tracing and locating





SPECIFICATIONS

• Camera	
Diameter	15.5 mm
Type	Fixed
Line Capacity	1" to 2 1/2" (25 mm to 64 mm)
• Push Cable	
Length	82' (25 m)
Diameter	0.28" (7.2 mm)
Minimum Bend Radius	1.5" (38 mm)
Cable Flexibility	Ultra Flex
• Sonde	512 Hz, Integrated
Weight	12.1 lb. (5.5 kg)
• Length	13.3" (337 mm)
• Width	8.8" (224 mm)
• Height	16.2" (411 mm)
Drum Diameter	12" (305 mm)

ORDER INFORMATION

CATALOG	DESCRIPTION	WEI	GHT
NO.		(lb.)	(kg)
70038	SeeSnake® NANOreel	12.1	5.5



ACCESSORIES

CATALOG NO.	DESCRIPTION
42778	30 mm and 25 mm Pipe Guide Set, 15 mm Camera, Pkg of 2
70723	Kit, Slipring Connector w/3m Cable
70718	Kit, CA-350 Adapter, Slipring Connector w/3m Interconnect Cable
67808	Kit, CA-350 Adapter w/Docking Handle
55898	micro CA-350 Inspection Camera
69758	Kickstand Accessory
71498	Spare, Slipring Connector
67307	Interconnect Cable, 3m















Scan for more information on HQx Live

RIDGID.COM/seesnake





