

811K/6A DIGITAL HIGH PERFORMANCE TRACING KIT

TESTING | TROUBLESHOOTING | ACCURACY

UNIVERSALLY COMPATIBLE.

The 811k/6A Digital High Performance Tracing Kit is a wire and pair tracing tool that is both universally compatible and virtually noise-immune. Whether tracking wires in a clear and quiet location or trying to find a wire in an area roaring with power hum and digital crosstalk, the 200XP probe and 77GX2 tone generator work efficiently. The tracing pair is also capable of working with any older type conventional tone probes and tone generators.

Features:

- High noise immunity.
- Adjustable to a wide range of applications.
- Flexible connection.
- ID577™ compatible.
- Universally compatible with older equipment.

ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
811K/6A	Digital High Performance Tracing Kit



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.

1.800.561.8187

www.itm.com

information@itm.com

811K/6A INFORMATION

Product Features:

- Trace wire pairs or cables even in areas with high electrical noise levels.
- Very high performance together, still work with all older tracing equipment.
- Crystal-controlled digital signal processing (DSP) accuracy.
- Selectable digital probe filtering allows users to choose performance.
- Single button probe function control.
- Power hum melts away with the press of a button.
- Works with butt sets for improved audibility in loud locations.
- Selectable power output levels in generator permit tailoring to application.
- Two-line telephone service indication.
- Short circuit check.
- Tone generator offers modular plug, modular jack or ABN alligator clip connection.
- Three selectable tone sending patterns.
- Auto-off battery saver function for probe (5 min) and generator (4 h).
- Low battery indication.

SPECIFICATIONS:

TONE PROBE

Probe tip resistance:	300 ohms minimum
Filter 2 out-of-band rejection:	30dB
Input impedance:	100M ohms
Gain:	35 decibels
Power:	One 9V battery, nominal life >50 h
Battery-saver time out:	5 minutes
Size:	1.25 x 1.375 x 9.75 inches
Weight:	Weight 4.7 ounces with battery

TONE GENERATOR

Output Voltage (Talk Battery into 600 ohms):	5.5 Vdc
Output Signal Power (600 ohms):	Hi Setting +8 dBm Low Setting +1 dBm
Output Frequency (nominal):	Tone alternating 577/984 Hz+/-1%
Output Warble Rate:	Slow 2.5 Hz Medium 6 Hz Fast 13 Hz
Output Voltage Protection:	60 Vdc
Power:	One 9V battery, nominal life >100 h
Auto Shut-Off (in Tone mode):	4 hours
Size:	4.0 x 1.65 x 1.5 inches 10.1 x 4.2 x 3.8 cm

TC811/6A 03/21



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.