

915CL OPTICAL FIBER CLEAVER

SPLICE AND CLEAVE FIBER THE RIGHT WAY!

FAST

Cleaved Fiber remains in the adapter ready to splice and is compatible with the 915FS, FSP200 or the 910FS fusion splicers.

ACCURATE

Precision-engineered blades accurately cleave fibers for minimal loss.

RELIABLE

Field tested to perform the dust bin safely collects end cuts.





915CL OPTICAL FIBER CLEAVER

BENEFITS

- Accurate Cleaves. Cleave multi-mode and single-mode fiber optic cables.
- Long Life. Blades rotate for longer life over 48,000 cleaves.
- Adaptable. Supports 250um, 900um fibers and loose tube fibers.
- Fast. For use with the 915FS, FSP200 or the 910FS Optical Fusion Splicer for maximum speed and efficiency with auto return mechanism.
- Dust bin. Safely collects end cuts during cleaving process.
- Fixed Clamp. Allows the technician to use the 915CL as a standalone cleaver.

SPECIFICATIONS:

APPLICABLE FIBERS:	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)
FIBER CLEAVED LENGTH	5mm - 20mm
CLADDING DIAMETER:	125µm
COATING DIAMETER:	0.25 mm and 0.9 mm
FIBER COUNT:	Single
CLEAVING ANGLE:	< 1.5°
BLADE LIFE	48,000 Cleaves
WEIGHT	0.56 lbs (255 g)
DIMENSIONS (HXWXD)	2.29 x 2.17 x 1.89" (58 x 55 x 48 mm)



FOR USE WITH THE 915FS, FSP200 OR 910FS FUSION SPLICERS

ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
915CL	915CL Optical Fiber Cleaver
915CL-Blade	Cleaving Wheel (915CL)
01332	250µm Adapter (Pair)
01333	900µm Adapter (Pair)
05801	Loose Tube Adapter (Pair)
03245	3mm Adapter (Pair)
PA1171	ProGrip 5-in-1 Fiber Optic Stripper

CAT. NO.	DESCRIPTION
PA1177	ProGrip 3-in-1 Fiber Optic Stripper
10997	Economy Fiber Optic Stripper
PA1511	Kevlar Cutter
MSS100	Mid Span Slitter
915CL-CLAMP	Fixed Clamp for 915CL with Screw
04268	Replacement Screw for Fixed Clamp

The 915CL is supplied with a fixed clamp and a mounting screw that the technician can use to permanently mount the fixed clamp to the cleaver. Shipped not assembled.

TC6580 03/23



Renewed Vision. **Innovation** Forward.

