

***Demand the Best. . . New!***

***Introducing the professional's new choice in high powered drain cleaning machines . . .***

## ***K-6200 Drain Cleaning Machine***

The RIDGID/Kollmann K-6200 drum style drum cleaner provides the professional with a powerful yet compact machine for cleaning 3" to 6" drain lines. Superior maneuverability and a small footprint allow easy access to tight work areas. It comes equipped with either IC (Inner Core) cable for ultimate flexibility or IW (Integral Wound) cable, a new more durable solid core alternative cable. Several new features include:

**New Torque Limiter** – Causes the drum to slow down when the blade becomes lodged in a blockage. Protects cable by limiting potential for cable flipover.

**Direct Drive Design** – Powerful 4/10 Hp universal motor and gearbox bear down as torque builds. Audible warnings let operator know when blockage is encountered. Drum requires no adjustments to stay aligned and tight on drive shaft. Makes easy work of tough blockages such as roots and hardened grease.

**Easy Maintenance Construction** – Drum separates from machine in seconds. Inner drum and guide tube easily removed to maintain or replace cable.

**Durable, Stable Design** – Low center of gravity frame design and custom Kollmann kickstand keep machine firmly anchored during operation. Rugged, corrosion resistant polyethylene drum is rust and dent proof. Double tubular frame is lightweight and designed for extra strength.

**Autofeed and Standard Accessories** – Powerful feed mechanism is built to last and is easily maintained. Autofeed, toolbox, and selection of cutters included in all models.

**Converts Easily to 1/2" Machine** – Accepts K-3800 drum, with adaptors, to run up to 90' of 1/2" cable for use in floor drains and other interior piping systems up to 4".



### ***Ordering Information***

#### **Machine Options – Power Feed**

| Catalog No.<br>115V | Model No.        | Description   |
|---------------------|------------------|---|
| 95737               | K-6200           | Machine w/5/8" Pigtail & Standard Accessories                     |
| 95732               | K-6200 w/C-24    | Machine, Standard Accessories and 5/8" x 100' Inner Core Cable    |
| 93557               | K-6200 w/C-24-IW | Machine, Standard Accessories and 5/8" x 100' IW Solid Core Cable |



***Demand the Best ... Demand***  
**RIDGID | Kollmann.**

# K-6200 Drain Cleaner

## Specifications

**Line Capacity** ..... 3" – 6" Lines, Up To 200 feet

**Drum Capacity** ..... 100' of 5/8" Cable

### Motor:

Type ..... 115V/60 Hz, Reversible,  
Universal AC Motor

Rating ..... 4/10 HP, 285 RPM

Amps ..... 5.6








**Weight** (Machine &  
100 ft of Cable) ..... 180 lbs.

**Length** ..... 29 1/2"

**Height** ..... 43.5" (max)

**Width** ..... 19"






**Tools and Replacement Blades — Fits C-24,  
C-25, C-26, C-27, C-24 IW, C25 IW, C-26 IW, C-27 IW,  
C-24HC, C-27HC**

|   | Catalog No. | Model No. | Description           | Replacement |         |
|---|-------------|-----------|-----------------------|-------------|---------|
|   |             |           |                       | Blade(s)    | Holder* |
|   | 92485       | T-403     | P-Trap Cutter, 3"     | 92835       | 92900   |
|   | 92490       | T-404     | P-Trap Cutter, 3 1/2" | 92840       | 92900   |
|  | 92495       | T-406     | Spear Blade           | 92850       | 92915   |
|  | 92500       | T-407     | Retrieving Auger      | —           | —       |
|  | 92505       | T-408     | Sawtooth Cutter       | 92890       | 92915   |
|  | 51762       | T-409     | H-D Bulb Auger        | —           | —       |
|  | 92510       | T-411     | Double Cutter, 2"     | 92815       | 92905   |
|   | 92515       | T-412     | Double Cutter, 2 1/2" | 92820       | 92905   |
|   | 92520       | T-413     | Double Cutter, 3"     | 92825       | 92910   |
|   | 92525       | T-414     | Double Cutter, 4"     | 92830       | 92910   |
|   | 92530       | T-416     | Double Cutter, 6"     | 92855       | 92910   |
|  | 92535       | T-432     | 3-Blade Cutter, 2"    | 92860       | 92895   |
|   | 92540       | T-433     | 3-Blade Cutter, 3"    | 92865       | 92895   |
|   | 92545       | T-434     | 3-Blade Cutter, 4"    | 92870       | 92895   |
|   | 92550       | T-436     | 3-Blade Cutter, 6"    | 92875       | 92895   |

## Optional Accessories

- Cat. #95812 Autofeed — K-6200
- Cat. #49032 Front Guide Hose Assembly
- Cat. #95797 Lifting Hook — K-6200
- Cat. #95792 Swivel Loading Wheel Assembly
- Cat. #95802 K-6200 Drum Assy. w/5/8" Pigtail
- Cat. #95807 K-3800 Drum Assy. w/6200 Adapters
- Cat. #95822 K-3800 to K-6200 Adapter Kit Only
- Cat. #59982 Cable Rust Inhibitor 1 QT.
- Cat. #95587 Cable Rust Inhibitor 1 Gal.

## Cables and Flexible Leaders

|   | Catalog No. | Model No. | Description   |
|---|-------------|-----------|---|
|  | 92460       | C-25      | 25' I.C. Cable (7,6m)                               |
|   | 92465       | C-26      | 50' I.C. Cable (15,2m)                              |
|   | 92470       | C-27      | 75' I.C. Cable (22,9m)                              |
|   | 43647       | C-24      | 100' I.C. Cable (30,5m)                             |
|  | 32737       | C-27HC    | 75' Hollow-Core (22,9m)                             |
|   | 58192       | C-24HC    | 100' Hollow-Core (30,5m)                            |
|  | 95762       | C-25 IW   | 25' I.W. Cable (7,6m)                               |
|   | 95757       | C-26 IW   | 50' I.W. Cable (15,2m)                              |
|   | 95752       | C-27 IW   | 75' I.W. Cable (22,9m)                              |
|   | 95747       | C-24 IW   | 100' I.W. Cable (30,5m)                             |
|  | 92555       | T-458     | 5/8" x 2' Leader                                    |
|  | 44122       | —         | 5/8" Pigtail  |
|   | 91047       | —         | 5/8" Cable Repair Coupling (Fits over end of cable) |



Standard Equipment Included In All Machine Options



Machine In Reclined Position

Distributor