

TEMPEST™ TIC 3.3

ECO-BOOST-SYSTEM

High Resolution Thermal imaging camera

Efficient and versatile = 3 buttons + 3.5" display

Particularly suitable for the First attack. TEMPEST TIC 3.3 offers unbeatable value and best quality, combined with all important features: ideal for firefighting, first attack, search for missing persons and fire...




Outstanding features:

- Compact 6.5 x 5.5 x 3.4"
- Lightweight 1.92 lbs with 2 batteries and side straps.
- Large 3,5" display for details visibility
- Widest detection range: -40 °F to +2100 °F
- Video recording, picture capture and image freeze
- Batteries: 6 year warranty, 5000 charging cycle
- Safe batteries (LiFePO4): for high temp operations
- Up to 8h running time (2 batteries) with Eco-Boost-System (up to 60% additional running time than previous model)
- Germanium window to protect the optics
- Removable Pistol grip option
- Boot time: less than 5 sec
- 3 Large buttons: easy to operate even with gloves
- **Functions:**
 - ON/OFF 0
 - Zoom x2 x4
 - Colorization selection (3 or 5 modes)
 - Image freeze / picture capture (option)
 - Video recording (option)
 - Replay picture and video on screen
 - Laser pointer (option)




Color schemes:

TEMPEST TIC 3.3 offers 3 color schemes as standard: Fire, Search, and Inverse +2 color schemes as option: Cold Finder and Multicolor



STD / FIRE: Dark Red >1560°F Red > 1250°F Orange > 930 °F Dark Yellow >660°F Yellow > 400°F White = Hot Black = cold




SEARCH: 2 hottest % colored in Red and the 5 following hottest % in Yellow-Orange.



COLD Finder: Blue color for coldest areas



INVERSE: Same as Fire scheme but White & Black are inversed: White = Cold Black = Hot



MULTICOLOR For Industrial: applications

3 Sensitivity modes with automatic switch according observed scene:

- -High sensitivity temperature range: -40 +300°F
- -Medium sensitivity temperature range: -40 + 950 °F
- -Low sensitivity temperature range: -40 +2100°F





Characteristics:

Tempest TIC	3.3 with Eco-Boost-System			
Dimensions	L.6.5 x W.5.5 x H.3.4" (H= +4.33" with optional pistol grip)			
Weight	1.92lbs with 2 batt / 1.73lbs with 1 batt (+0.37lbs with optional pistol grip)			
Display	3,5" LCD / 320 x 240 (76 800) px / Backlighted / Brightness: 74.32 cd/ft ²			
Frequency	60Hz Fps			
T°C Range	-40° to +2100°F			
Colorization	Std: Fire, Search, Inverse Option: Cold Finder and Multicolor			
	Housing			
Material	PUR / Elastomer			
Drop Test	6.5 ft on concrete			
IP	IP67 / 3.2ft - 30 Minutes			
Heat resistance	300°F for 15min / 500°F for 5min			
	Sensor			
Micro bolometer type	Uncooled 17µ Amorphous Silicon aSi Resolution 384 x 288 (110 592 px)			
	Uncooled 17μ Amorphous Silicon aSi			
type	Uncooled 17μ Amorphous Silicon aSi Resolution 384 x 288 (110 592 px) 7 – 14 μm NETD: <50mK (<0.05 °C)			
Spectral range	Uncooled 17μ Amorphous Silicon aSi Resolution 384 x 288 (110 592 px) 7 – 14 μm			
type Spectral range T°C sensitivity	Uncooled 17µ Amorphous Silicon aSi Resolution 384 x 288 (110 592 px) 7 – 14 µm NETD: <50mK (<0.05 °C) Optics Germanium Carbon Coated			

Rechargeable batteries	LiFePO ₄ (Lithium Iron Phosphate = safety VS fire), 2.5Ah at 6.6V, 0.19lbs					
Running time (68°F) with Eco-Boost- System since October 2018	Without video/photo functions: >8h (2 batt) / >4h (1 batt) With video/photo functions: >6h (2 batt) with non-active video >5h (2 batt) with recording video					
Boot time	< 5 seconds					
Charging voltage	12 / 24 VDC or 100-240 VAC					
Charging time (for 2 batt. / half for 1 batt.)	Charging bay: ~1h30 Mains charger: 100% in ~2h, 90% in ~1h30, 80% in ~1h20					
Charging cycles	> 5000					
Memory (optional)	8GB internal SD card (8h video or 1000 pics)					
Warranty	5 years on camera_/ 6 years on batteries / 10 years on thermal senso / 1 year on accessories (chargers, charging bay, etc)					
	Options					
Removable pistol gri	ip Picture capture and/or video recording (8GB capacity)					
Neck strap in flame retardant material	Vehicle charging bay or mains charger					
1 or 2 Retractable lanyards	Carrying case IP67					
Protection hood	Wireless video transmission to computer, tablet or smartphone					
Analogue output (NTSC or PAL)						

General



Energy concept

LiFePO4 batteries (lithium-iron-phosphate). **Benefits:**

- -Very long lifespan guaranteed 5000 charging cycles (~10 years)

Picture capture & Video recording

Pictures (up to 1000) and Video (up to 8h) can be:

- viewed on the camera screen during operation
- Live Pictures can be sent to a computer, tablet or smartphone thanks to optional wireless stick.
- Downloaded into a computer via a USB cable







High-Gain

Freeze/

Very space-saving mountable! Power supply 12/24 VDC or 100-240 VAC. Can charge up to 4 batteries at the same time (2 in the camera and 2 spares)

Camera standard features:

	Color modes		Features								
Description	Color modes	Optional color modes	Max color modes	Battery	Freeze mode	Side trap	Video recording	Picture capture	Laser	Zoom	USB cable
TEMPEST TIC 3.3			5	2	V	2				V	
TEMPEST TIC 3.3 L	& Search		5	2	V	2			V	V	
TEMPEST TIC 3.3 V	& Cold	5	2	V	2	V	V		V	V	
TEMPEST TIC 3.3 VL		5	2	V	2	V	V	V	V	V	

V= Video + Picture

L = Laser

Camera optional accessories:

Callie	ia optionai	accessories.
	Wireless Transmission kit	Only compatible with cameras equipped with Video recording
	Pack of 2 spare batteries	
U	Cable charger	Available in 12/24V or 100V-240V
GAZA .	Watertight Carrying case	IP67
(mg)	Vehicle charging bay	Charge batteries inside the camera
*	Laser pointer	Only for 3.3 and 4.3 models

	Vehicle charging bay with additional slots	Charge batteries in the camera + 2 extra spare batteries
	Power supply for charging bay	Exist in 12/24V or 1 100V-2400V with US or EU plug
	Retractable lanyard	1.1lbs or 2.2lbs tension force
1	Neck strap	Fire-proof (Kevlar)
	Protection hood	Increases exposure time x2 to high temperatures
1	Removable pistol grip	Pistol grip = 0.37lbs Incl. mounting tool







