

ACL 350 Digital Static Locator

Measure electrostatic charges with precision!



Easy to Use:

Discharge static from your body by touching a grounded metal object.

Press the "ZERO" button twice. From a distance, point the electrode in the direction of the target and move toward it, observing the value on the LCD window. Press and hold the "PWR ON/HOLD" button and note reading from $1/10"$ to 8.5", making sure to properly multiply reading according to chart in the user manual.

See manual for details.

Product #350 includes carrying case, 9-volt battery, and NIST-traceable calibration certificate.

The ACL 350 is the ideal electrostatic locator meter for applications in which a precise measurement is required. The 3.5 digit LCD displays both negative and positive polarities. By spacing the meter from $1/10"$ to 8.5", a range of 0-80,000 volts can be measured. Utilizing the "HOLD" function allows the user time to record the precise voltage. Easy to use and lightweight, this battery-powered meter can be quickly re-zeroed, allowing for repetitive measurements. The ACL 350 can be used for determining the source of electrostatic charges in ESD-controlled environments or in other areas where static is of concern. It is perfect in electronic component production and assembly areas, textiles, packaging, engineering labs, and printing.

- ❖ **3½ digit LCD**
- ❖ **Accuracy: $\pm 10\%$**
- ❖ **Range: 0 ± 80,000 volts**
- ❖ **Low battery indication**
- ❖ **Powered by 9-volt battery**
- ❖ **Quick zero function**
- ❖ **Hold function**
- ❖ **Automatic shut off after 90 seconds**
- ❖ **Weight: 5 ounces**
- ❖ **Size: 4.2" x 2.4" x 0.9"**
- ❖ **Made in the USA**



ACL Staticide



ACL Inc. registered to
ISO-9001: 2015
Certificate No. 10002746
Date of issue: 2015-09-24