

# HVAC CLAMP METER WITH DIFFERENTIAL TEMPERATURE

# CL450



-40°F - 1832°F  
(-40°C - 1000°C)

T2 - T1



# KLEIN TOOLS®



1.800.561.8187 [www.itm.com](http://www.itm.com)

information@itm.com

# THE GAME CHANGER IS HERE!

The dual-display **CL450 HVAC Clamp Meter** is a game changer for the HVAC professional. This True RMS, CAT IV meter offers DC microamps, differential temperature, digital temperature calibration, inrush current, and many other easy to perform functions for key HVAC applications.



**DC Microamps**

- Measures DC current across the flame sensor
- Confirms flame rectification



**Differential Temperature**

- Dual display reads T1 and T2 measurements as well as displays the differential temperature
- Used to troubleshoot many HVAC applications



**Inrush Current**

- Measures surge when electrical device is started up
- Critical for the installation, diagnostics and maintenance of electrical motors



**Digital Temperature Calibration**

- Temperature calibration corrections in field with a push of a button
- No more adjusting the potentiometer with a screwdriver

# HVAC CLAMP METER WITH DIFFERENTIAL TEMPERATURE

# CL450

## HVAC|R

| Measurement                     |  |                                    |
|---------------------------------|--|------------------------------------|
| AC/DC Voltage                   |  | 1000V                              |
| AC + DC Voltage                 |  | •                                  |
| AC Current                      |  | 600A                               |
| Resistance                      |  | 60MΩ                               |
| DC Millivolts                   |  | •                                  |
| DC Microamps                    |  | •                                  |
| True RMS                        |  | •                                  |
| Non-Contact Voltage Testing     |  | •                                  |
| Low-Pass Filter                 |  | •                                  |
| Low Impedance                   |  | •                                  |
| Audible Continuity              |  | •                                  |
| Backlight                       |  | •                                  |
| Differential Temperature        |  | -40° - 1832°F<br>(-40° - 1000°C)   |
| Digital Temperature Calibration |  | •                                  |
| Auto-Ranging                    |  | •                                  |
| Range Hold                      |  | •                                  |
| Data Hold                       |  | •                                  |
| Diode Test                      |  | •                                  |
| Capacitance Test                |  | •                                  |
| Frequency/Duty Cycle            |  | •                                  |
| Max/Min Value                   |  | •                                  |
| Relative Mode                   |  | •                                  |
| Auto Power-Off                  |  | •                                  |
| LCD Display Count               |  | 6000                               |
| Durability                      |  |                                    |
| Drop Protection                 |  | 6.6 ft.<br>(2 m)                   |
| Safety Rating                   |  | CAT IV<br>600V<br>CAT III<br>1000V |



# HVAC CLAMP METER WITH DIFFERENTIAL TEMPERATURE

# CL450

## HVAC|R



## Additional accessories available for this HVAC Clamp Meter



Replacement K-Type Thermocouple  
69435



K-Type Temperature Pipe Clamp with Adapter  
69140



Adapter, K-Type to Banana Plug  
69146



High Temperature K-Type Thermocouple with Adapter  
69142



K-Type Temperature Probe with Adapter and Case  
69144



Magnetic Hanger  
69417



*Thermocouples are NOT intended for use on people or animals.*



| Cat. No. | UPC# 0-92644+ | Description                                  | Includes   |
|----------|---------------|--|--|
| CL450    | 69063-1       | HVAC Clamp Meter w/ Differential Temperature | Carrying case, test leads, 2 thermocouples, 3 AAA batteries. |

| Accessories |               |   |                   |
|-------------|---------------|---|-------------------|
| Cat. No.    | UPC# 0-92644+ | Description                                     | Temperature Range |
| 69435       | 69230-7       | Replacement K-Type Thermocouple                 | -30 to 482° F     |
| 69140       | 69067-9       | K-Type Temperature Pipe Clamp w/ Adapter        | -4 to 212° F      |
| 69142       | 69068-6       | High Temperature K-Type Thermocouple w/ Adapter | 32 to 896° F      |
| 69144       | 69069-3       | K-Type Temperature Probe w/ Adapter & Case      | -58 to 1112° F    |
| 69146       | 69070-9       | Adapter, K-Type to Banana Plug                  | n/a               |
| 69417       | 69417-2       | Magnetic Hanger                                 | n/a               |

1.800.561.8187

www.itm.com



© 2018 Klein Tools, Inc.  
Lincolnshire, IL 60069-1418  
06239 Rev 01/18 A

information@itm.com