



CLASSIC SERIES CLA-150

MODEL	NOMINAL STEADY-STATE UV-A INTENSITY at 15 in (38 cm) ①	UV-A COVERAGE AREA at 15 in (38 cm) at minimum 1,200 μW/cm²
CLA-150	7,000 μW/cm ²	7 in (17.78 cm)

 Φ UV-A intensity reading taken with the Spectroline® AccuMAX $^{\bowtie}$ Series meter, and is factory set to the value shown.

Light Source:	4 UV-A LED's
Lamp Style:	Handheld lamp
Lamphead Diameter:	4.4 in (11.18 cm)
Length:	6.7 in (17 cm)
Width:	3.4 in (8.6 cm)
Height:	7.45 in (18.9 cm)
Weight:	2.05 Lb (930 g)
Power Requirements:	90 - 270 VAC, 50 TO 60 Hz


CLA-150


Classic Series Dual Function LED Inspection Lamp Kit


Comes complete with Classic Series Dual Function LED Inspection Lamp with lanyard, Power Supply, AC Cord set, UV Absorbing Spectacles, Carrying Case For Spectacles, Protective Carrying Case.



UV-A Beam Profiles







SPECTRO-UV

DISTRIBUTED BY:

NDT 2/23 A2032023 PRINTED IN USA

