



# CS-5000

## TRACE AND LOCATE WITH CONFIDENCE

### Safe. Accurate. Reliable.

#### CS-5000 **CIRCUIT SEEKER™**

- Superior sensitivity and functionality providing accurate tracing and locating
- Auto Gain Option – Automatically seeks the strongest signal identifying the target breaker, improving locating accuracy
- Supports transmitter-to-receiver distances up to 4 miles for closed circuit tracing
- Rated for 600VAC/DC
- Works on de-energized circuits, no need to have to have the power on
- Works on live circuits without disrupting service

#### **Ergonomic**

- Front facing LED linear array receiver display promotes good working posture reducing hand strain
- Handle design creates comfortable, easy grasp to reduce hand fatigue

#### **Versatile**

- Dual Notification: Visual (bright LEDs) and distinctive audio tone, assist the operator in challenging work environments
- Traces concealed wiring, locates junction boxes, and finds breakers for live or open circuits



# CS-5000

TRACE AND LOCATE WITH CONFIDENCE

## Dual Modes

Search mode and breaker mode



## Battery Life Indicator

Maximizes productivity



## Ergonomic Over-Molded Grip

Results in comfort for the operator



## Line Status

Reads live or open to determine an energized or de-energized circuit

## Front Facing LED Linear Array

Indicates relative signal strength

## Circuit Seeker Family



## ORDERING INFORMATION

CAT. NO.	UPC NO.	DESCRIPTION
CS-5000	783310085133	CIRCUIT SEEKER KIT (Transmitter, Receiver, (2) Alligator Clips, AC Blade, AC Plug Adapter, (2) Extension Leads, and Carrying Case)
08435	783310084358	TRANSMITTER
08436	783310084365	RECEIVER
10057	783310100577	(2) ALLIGATOR CLIPS
10054	783310100546	AC BLADE
12852	783310128526	AC PLUG ADAPTER
12853	783310128533	(2) EXTENSION LEADS
08437	783310084372	CARRYING CASE
CS-8000	783310121268	CIRCUIT SEEKER KIT (Transmitter, Receiver, (2) Alligator Clips, AC Blade, AC Plug Adapter, (2) Extension Leads, and Carrying Case)

## SPECIFICATIONS

Voltage Rating:	600V AC/DC
Tracing Range Open Line Mode:	Up to 3 m (10 ft) with a metallic connection to ground; 0.3 to 0.9 m (1 to 3 ft) with a capacitive ground reference
Tracing Range Live Line Mode:	Up to 6 m (20 ft) from circuit
Auto Power Off Intervals (Transmitter):	4 Hours
Auto Power Off Intervals (Receiver):	30 minutes without signal
Operating Conditions:	(32 °F to 122 °F)
Battery Type:	Transmitter: Two 1.5 V AA batteries Receiver: Two 1.5 V AA batteries
Certifications:	CE, CSA

Professional. Nothing Less.™



1.800.561.8187

www.itm.com

information@itm.com