

***Now, Just One
Intensity Reading
Will Do!***



DM-365XA UV Radiometer

- Provides *unmatched* overall accuracy of better than $\pm 5\%$, traceable to NIST
- Ideal for NDT and QC inspections
- Complies with both MIL and ASTM standards
- Easy-to-read LED display
- Water/liquid-resistant

*Manufactured for high performance by Spectronics Corporation
...the world leader in UV technology since 1955*

Discard those pocket calculators, conversion charts and tables. The DM-365XA is the *only* instrument you'll need to perform your daily black light lamp calibrations. Analog meters are history! *True* digital UV readings come from Spectronics Corporation, the company that *invented* the digital UV radiometer! The DM-365XA is truly a meter for the 21st Century!

Unmatched accuracy — Meter calibration by pyroelectric method provides superior linearity and controlled spectral response. Auto-zeroing feature and reliable electronic/electro-optic circuitry provide excellent signal-to-noise ratio. High-quality interference filter ensures closely controlled spectral coverage (320 to 400nm) and eliminates sensitivity to infrared.

Longer sensor life — Rugged, silicon photodiode is sealed and fixed in a metal/quartz package to protect against adverse effects of shock and humidity, eliminating the possibility of photodiode fracture. As a result, the sensor lasts longer.

Truer readings — Upgraded sensor components, sealed silicon photodiode and new calibration light source, among other improvements, provide error-free readings and more repeatable results. True values can be obtained with just one reading — *without* requiring a second reading to compensate for infrared sensitivity.

Maximum durability — The DM-365XA radiometer's solid-state circuitry is housed within a durable polycarbonate housing to protect against shock damage.

Other features include:

- Liquid-resistant sensor housing prevents moisture contamination
- Calibration upgrade — 365nm calibration light source utilizes an improved cooling system and a more collimated light profile



Avoid a "balancing act."

Use the Spectroline Model VF-100 Spec-Stik™ MIL-STD verification fixture to calibrate your lamps at *exactly* 15 inches (38.1cm)!

Technical Data

Readout Unit Specifications

Display	4½ digit LED
Conversion Rate	3 readings per second nominal
Resolution	1 part in 1,999
Temperature Coefficient	±(0.025% of reading +0.1 digit)/°C (0 to 50°C)
Case Dimensions	7¼L x 3½W x 2"H (18.4L x 8.9W x 5.1cmH)
Total Net Weight	1 lb. (0.45 kg)

Sensor Head Specifications

Overall Accuracy	Better than ±5% with reference to NIST standards
Spectral Range	320-400 nanometers (nm)
Measuring Range	0-19,990 µW/cm²
Resolution	10 µW/cm²
Filter	High quality, vacuum-deposited, interference type
Angular Response	Cosine
Temperature Coefficient	±0.20%/°C (0 to 50°C)
Power Requirements:	
4 non-rechargeable "AA" size alkaline battery cells are included as standard	
4 rechargeable "AA" size nicad battery cells and a recharger are available as an option	
Reference Conditions:	
Temperature 23°C ±1°C	
Relative Humidity 30 to 60%	
Atmospheric Pressure 575 to 800mm Hg to 7,500 ft. (2,286m) altitude	
Sensor Head Dimensions:	3L x 2W x 0.7"H (7.6L x 5.1W x 1.8cmH)
Sensor Cord Length	3 ft. (0.9m)