

P/N: DM92

Copyright

© 2014, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: DM92

Release:

Commit: 21224

Language: en-US

Modified: 2014-11-27

Formatted: 2014-12-01

Corporate Headquarters

FLIR Systems, Inc.

27700 SW Parkway Ave.

Wilsonville, OR 97070

USA

Telephone: +1-503-498-3547

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Part number	DM92
Part name	Industrial Digital Multimeter with LoZ and VFD Mode
Part description	<p>The FLIR DM92 is an industrial-grade digital multimeter built for durability to ensure longevity in rugged environments.</p> <ul style="list-style-type: none"> • Variable frequency drive (VFD) mode filters noisy variable-frequency drives and enables accurate voltage and frequency measurements for maintenance and troubleshooting tasks. • Low impedance (LoZ) eliminates ghost voltage errors from long wires that share a conduit. • Convenient LED work lights assist with focusing on test leads without the need to also hold a flashlight. <p>Functions: DC voltage, AC voltage, DC current, AC current, resistance, type K thermocouple contact temperature, capacitance, frequency, diode, continuity, duty cycle.</p> <p>Features: VFD mode, LoZ mode, minimum, maximum, average recording, auto power off, hold, relative, peak hold, store, recall.</p>

Measurement	
Maximum voltage	1000 V DC or 1000 V AC RMS
Display count	4000/40 000
Frequency counter	400.00 Hz ± 5 digits 4.0000 kHz ± 5 digits 40.000 kHz ± 5 digits 100.00 kHz ± 5 digits



FLIR DM92: Industrial Digital Multimeter with LoZ and VFD Mode

P/N: DM92

© 2014, FLIR Systems, Inc.
#DM92; r. /21224; en-US

Measurement	
Resistance	400.0 Ω ± (0.2% + 2 digits) 4.000 kΩ ± (0.2% + 1 digit) 40.00 kΩ ± (0.2% + 1 digit) 400.0 kΩ ± (0.2% + 1 digit) 4.000 MΩ ± (1.0% + 1 digits) 40.00 MΩ ± (2.0% + 20 digits)
Continuity check	400.0 Ω ± (0.2% + 2 digits)
Diode test	2.000 ± (1.5% + 2 digits)
Capacitance	40.00 nF ± (1.2% + 20 digits) 400.0 nF ± (0.9% + 2 digits) 4.000 μF ± (0.9% + 2 digits) 40.00 μF ± (0.9% + 2 digits) 400.0 μF ± (0.9% + 2 digits) 4.000 mF ± (1.2% + 20 digits) 40.00 mF ± (2.0% + 20 digits)
Temperature	-328 to 2192°F ± (1.0% + 36 digits), -200 to 1200°C ± (1.0% + 20 digits)
Measuring rate	10 samples per second
Meter data	
Category rating	CAT IV—600 V, CAT III—1000 V
Data recording	20 000 points (125 days maximum)
Warranty	Limited lifetime warranty
Calibration cycle:	Once per year, recommended
Certifications	
Certifications	UL, CE, FCC, CB
Safety standards compliance	IEC 61010-1 CAT IV—600 V, CAT III—1000 V, IEC 61010-2-033
Power system	
Power requirements	6 × 1.5 V AAA alkaline batteries
Battery life	Approximately 100 hours with batteries (backlight and work light off)
Auto power off	Default: 10 minutes
Environmental data	
Operating ambient temperatures and relative humidity (RH)	14–86°F (-10 to 30°C), <85% RH 86–104°F (30–40°C), <75% RH 104–122°F (40–50°C), <45% RH
Storage temperature and RH	-22 to 140°F (-30 to -60°C), 0–80% RH (batteries not fitted)
Temperature coefficient	0.1 × (specified accuracy)/°C, <18°C, >28°C
Operating altitude	6560' (2000 m)
Pollution degree	2



FLIR DM92: Industrial Digital Multimeter with LoZ and VFD Mode


P/N: DM92

© 2014, FLIR Systems, Inc.

#DM92; r. /21224; en-US

Environmental data	
EMC	EN61326-1
Shock vibration	Per MIL-PRF-28800 for a Class 2 instrument
Meter physical data	
Weight	16.4 oz. (465 g) including batteries
Dimensions (H x W x L)	2.0" x 3.2" x 7.4" (52 mm x 83 mm x 188 mm) with holster
Material	PC-ABS, TPE
Color	Gray and black
Shipping information	
Packaging type	Color box with view of product in clamshell
Packaging contents	DM92 FLIR meter, TA80 premium test leads, 6 x AAA Energizer batteries, user manual/CD
Packaging weight	1.04 kg (2.29 lb.)
Packaging dimensions (H x W x L)	11 cm x 14 cm x 32 cm (4.3" x 5.5" x 12.6")
Carton weight	13.5 kg (29.5 lb.)
Carton dimensions (H x W x L)	13 7/8" x 11 1/2" x 24 1/8"
Carton quantity	12
EAN-13	0793950370926
UPC-12	793950370926
Country of Origin	Taiwan
Tariff Code	9030310000
Technical support	
Website	http://support.flir.com
E-mail	T&Msupport@flir.com
Phone	855-499-3662
Repairs	repair@flir.com
Accessories	
TA10. EVA Protective case for DM9x and IM7x Series	
TA50. Magnetic Hanging Strap	
TA60. Thermocouple Adapter with Type K Probe	
TA70. CAT IV Insulated Alligator Probes (Slip On)	
TA80. CAT IV Silicone Test Leads	

© 2014, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without written permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values. Products may be subject to regional market considerations. License procedures may apply. Product may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions. Diversion contrary to US law is prohibited.



Modified Date Monday, August 18, 2014	Modified By T&M Engineering
Description FLIR DM92, Units in mm	

