

**Item # GSCP-150152-5, 1 ½ in. Stainless Steel Precision Sanitary Clamp Flowmeter**

This 1 ½ in. Tri-Clover Sanitary meter is for applications that do not require a 3A Approval. Comes with a GG510 standard display.

**Specifications**

<b>Design Type</b>	Turbine
<b>Inner Diameter</b>	1 ½ in.
<b>Fitting</b>	Sanitary Clamp 1 ½ in.
<b>Accuracy</b>	±0.5 % Linearity
<b>Flow Range</b>	17.7 to 177 GPM 67.0 to 670 LPM
<b>Repeatability</b>	±0.1 %
<b>Operating Temperature</b>	-100 to +185 °F -74 to +85 °C
<b>Frequency</b>	100 to 1000 Hz
<b>Recommended Strainer Size</b>	18 mesh
<b>Display</b>	LCD - GG510 Transmitter
<b>Reads</b>	Gallons Litres
<b>Electronic Choice</b>	GG510 - Standard Display (Local) GA500 (Remote) GG500 (Remote) GX500 (Remote) SC500 (Remote)
<b>Sensor</b>	Standard Pickup
<b>Pressure Rating</b>	Limited by fitting size, clamp size & temp.
	316 Stainless Steel Housing CD4MCu Stainless Steel Rotor

<b>Wetted Materials</b>	316 Stainless Steel Rotor Supports 316 Stainless Steel Shaft PTFE Sleeve Bearings 440C Stainless Steel Thrust Bearings
<b>Typical K-Factor</b>	340
<b>Model</b>	GSCP-150152-5
<b>Approvals</b>	N.I.S.T.
<b>Popularity</b>	<b>Most Popular</b>