

GT-12A NON-CONTACT VOLTAGE DETECTOR

50 TO 1,000 V (AC)



FASTER

- Single button operation.

SAFER

- CAT IV 1,000 V rated for maximum safety.
- Self tests every 2 seconds for accurate results every time.

EASIER

- Auto power off extends battery life¹.



Intertek
4006915



GREENLEE[®]

A Textron Company

www.**itm**.com

information@itm.com

1.800.561.8187

GT-12A

NON-CONTACT VOLTAGE DETECTOR



FEATURES

- Patented automatic self-test
- Bright LEDs flash and audible alarm sounds if AC voltage is present
- Silent mode for use in quiet areas
- Safe, non-contact voltage detection
- Automatic shut-off extends battery life¹
- Lifetime Warranty²
- Designed and assembled in USA

Large, easy-to-handle battery cover.

High brightness LEDs for visibility from any angle.



Rugged, ultrasonically-welded construction.

SPECIFICATIONS

Voltage Detection	50 V to 1,000 V (AC)
Frequency	50 Hz to 500 Hz
Measurement Category	CAT IV, 1,000 V
Battery Type	2 x AAA (included)

ORDERING INFORMATION

CAT. NO.	UPC NO.	DESCRIPTION
GT-12A	00890	Detector, Voltage Non-Contact

¹ Shut off occurs after 5 minutes of inactivity.

² Terms and conditions apply. See online or full-line catalog for more details.

