



The re-positionable configuration of the Heel Grounder extends the life of the product and the elastic loop provides a secure and comfortable fit. This quality Heel Grounder features a durable three-layer sole and a 24 inch conductive ribbon. 1 or 2 Megohm Resistor. Lot coded for QC traceability. Heel grounders

Properties	Typical Value	Test Method
Elastic Hook and Loop	3/4"	
Elastic Strap	Black	
Sole Interior	Non-marking	
Sole Exterior	<1x 10 ⁶ ohms	
Total Grounder	<1.2 x 10 ⁶ ohms	ESD-SP9.2, ESD TR53

Item	Description
HGC1M	Cup Style Heel Grounder, 1 Megohm Resistor
HGC2M	Cup Style Heel Grounder, 2 Megohm Resistor

UL Listed

are UL listed.


Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- · Make certain that you are not in contact with grounded objects other than through the ESD Series



Elastic Hook and Loop Strap for Comfort and Visibility



Wider Sole for Larger Contact Surface

Unless otherwise noted, tolerance ± 10%

Specifications and procedures subject to change without notice.



926 JR Industrial Drive, Sanford, NC 27332

HGC1M CUP STYLE HEEL GROUNDER

WEB SITE: StaticControl.com PHONE (919) 718-0000

DRAWING NUMBER HGC1M

DATE October 2015



Listing #90P1