

HI9126

Portable pH/mV Meter

- **CAL Check™**
 - Alerts users of calibration status
- **Backlight**
 - Backlit, multi-level LCD display
- **Battery Error Prevention System (BEPS)**
 - Automatically shuts off meter when battery is too low to take accurate readings
- **Battery indicator**
 - Battery percentage displayed on startup
- **Help feature**
 - Tutorial messages displayed on LCD

The HI9126 includes Hanna's exclusive CAL Check technology. CAL Check monitors the pH bulb every time the instrument is calibrated. In the event of a dirty pH electrode, CAL Check warns users that maintenance may be needed.

Calibrated buffers are continuously displayed in measurement mode to remind users of the instrument's calibration point. Users can easily determine if readings are taken too far outside the calibration range.

The HI9126 can store and recall a reading at the touch of a button and features a real-time clock.

HI9126 utilizes the HI1230B double junction pH electrode. The double junction design helps to minimize junction contamination for consistently accurate results. The HI9126 can also measure ORP in the mV range using an optional ORP probe.



Specifications

	HI9126
pH*	Range -2.00 to 16.00 pH
	Resolution 0.01 pH
	Accuracy ± 0.01 pH
	Calibration automatic, one or two-point with seven standard buffers available (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45) and two custom buffers
	Temperature Compensation automatic or manual from -20.0 to 120.0°C (-4.0 to 248.0°F)
mV	Range ± 699.9 mV; ± 1999 mV
	Resolution 0.1 mV; 1 mV
	Accuracy ± 0.2 mV; ± 1 mV
Temperature*	Range -20.0 to 120.0°C; -4.0°F to 248.0°F
	Resolution 0.1°C; 0.1°F
	Accuracy ± 0.4 °C; ± 0.8 °F
Additional Specifications	pH Electrode HI1230B PEI body pH electrode with BNC connector and 1 m (3.3') cable (included)
	Temperature Probe HI7662 stainless steel temperature probe with 1 m (3.3') cable (included)
	Slope / Offset Calibration from 80 to 108% / ± 1 pH
	Input Impedance 10^{12} Ohm
	Battery Type / Life 1.5V (3) AAA / approximately 200 hours of continuous use without backlight (50 hours with backlight)
	Auto-off after 20 minutes of non-use (can be disabled)
	Environment 0 to 50°C (32 to 122°F); RH max 100%
	Dimensions / Weight 185 x 72 x 36 mm (7.3 x 2.8 x 1.4") / 300 g (10.6 oz.)
Ordering Information	HI9126 is supplied with HI1230B pH electrode, HI7662 temperature probe, HI70004 pH 4.01 buffer solution sachet, HI70007 pH 7.01 buffer sachet, HI700601 electrode cleaning solution sachet, 100 mL plastic beaker, 1.5V AAA batteries (3), instructions and hard carrying case.

* Limits will be reduced to actual sensor limits



1.800.561.8187

www.itm.com

information@itm.com