

**FLUKE**®

TECHNICAL DATA

# Fluke ii915, ii905, and ii500 Acoustic Imagers



## SOUNDSIGHT™ TECHNOLOGY

### ACOUSTIC IMAGING

Blended live SoundMap™ with visual image

### DISPLAY

7-inch 1280 x 800 LCD with capacitive touchscreen

### LEAKQ™ MODE

Leak quantification: on-device estimated leak size and cost indications

### MECQ™ MODE

Mechanical inspection: on-device feature to detect and document mechanical issues, available on ii915

### PDQ MODE™

Partial discharge: on-device PD classification, available on ii915

SoundSight™ refers to the Fluke technology of converting sound waves to a visual image.

**The all-in-one tool you have been looking for to visualize leaks, partial discharge, and mechanical issues.**

## **Leaks: Hidden Costs Due to Leaks in Compressed Air, Gas, Steam, and Vacuum Systems.**

While most manufacturers know these leaks exist, addressing them has been time-consuming and tedious. With the Fluke ii Series and minimal training, your maintenance technicians can begin checking for leaks during their typical maintenance routine—even during peak operation hours. The ii Series Acoustic Imagers let technicians see sound as they scan hoses, fittings, and connections for leaks. Its built-in acoustic array of tiny sensitive microphones generates a spectrum of decibel levels per frequency. Based on this output, an algorithm calculates a sound image, known as SoundMap™, that is superimposed on a visual image. The SoundMap is automatically adapted depending on the frequency level selected so that background noise is filtered out, making it incredibly simple to detect compressed gas leaks.

1.800.561.8187

www.itm.com

information@itm.com



**Mechanical: First-Line Inspection to Locate Potential Mechanical Issues Early and Avoid Unplanned Downtime**

Conveyor systems, with their vast size and intricate components, often pose a maintenance challenge, threatening to disrupt production and cause unplanned downtime. The Fluke ii915 with MecQ™, a game-changer in the field, enables efficient scanning of large areas, detecting and documenting potential issues for more targeted maintenance. With its contactless scanning and advanced noise filtering, the Fluke ii915 Acoustic Imager with MecQ™ Mode ensures safety and delivers clear images even in high-noise environments. By detecting areas of concern early on, it instills confidence in its users, enabling proactive measures to prevent costly problems, surpassing traditional methods. For professionals seeking to ensure seamless operation of large conveyance systems, the Fluke ii915 Acoustic Imager with MecQ™ is the ultimate choice.

**Partial Discharge: The Invisible Threat... Now You Can See**

Partial discharge, a serious issue that can lead to arc flash fires, blackouts, explosions, and danger to life, is now a visible threat. Whether you are inspecting insulators, transformers, switch gears, or high-voltage powerlines, the Fluke ii915 Acoustic Imager with PDQ Mode™ is your proactive tool. This tool, designed for high-voltage electricians, electrical test engineers, and grid maintenance teams, translates the sound of partial discharge into visuals that pinpoint the location. With an extended frequency range of 2-100 kHz, the ii915 enables early detection of potential problems, empowering you to plan maintenance and prevent catastrophic events.



	ii500	ii905	ii915
<b>LeakQ™</b>	Scale (1-10)	Leak size scale, leak rate, and leak cost estimation	Leak size scale, leak rate, and leak cost estimation
<b>PDQ Mode™</b>			•
<b>MecQ™</b>			•
<b>Wi-Fi</b>		•	•
<b>Frequency</b>	2 to 52 kHz	2 to 65 kHz	2 to 100 kHz
<b>Detection Range</b>	Up to 50 meters (164 feet)*	Up to 70 meters (230 feet)*	Up to 120 meters (393 feet)*
<b>Visual Camera Resolution</b>	0.3 MP	5.0 MP	5.0 MP
<b>Battery Life</b>	6 hours	6 hours	6 hours
<b>Memory</b>	20 GB	32 GB	32 GB
<b>Tripod Connector</b>		•	•

\*Depending on ambient conditions





**Large 7" touch screen**

High resolution 7" capacitive, full color touch screen, supports interaction with interface menu.

**Operating time**

Stay powered all day with six hours of operating time

**One button capture image**

Capture images on-the-go with one click, no need to navigate the menu for image capture

**Intuitive user interface**

Easy to use with minimal training.

- Features supporting common workflows
- Unique customizable frequency band filter
- On-device real time data
- Customizable profiles for different inspection types

**Ergonomic to use**

Adjustable hand strap and adjustable neck strap

**Tripod connector**

ii915 and ii905 models come with standard 1/4"-20 UNC threaded hole for easy tripod mounting and clear images or video

**Annotate and tag**

Tag your inspections by adding photo notes, asset identifiers, text notes, and follow-up actions, including priority. Use QR codes to easily identify your inspections. No hassle or errors with seamless integration using the FlukeConnect™ desktop and online reporting software.

**Reduce the frustration of unplanned downtime in four easy steps**

**1. Locate**

Quickly and easily scan areas and pinpoint where unusual sounds are coming from – even those sounds out of range for human hearing.

**2. Document**


Take a screenshot of the point of interest. Then annotate and tag the photo to define follow-up action and urgency.

**3. Share**

Share the annotated screenshots with your team so they can respond and schedule maintenance.

**4. Repair**

Investigate the pinpointed areas further during planned downtime to determine what the problem is and proactively fix it.



## Specifications

Key Features	ii500	ii905	ii915
<b>Sensors</b>			
Frequency band	2 kHz to 52 kHz	2 kHz to 65 kHz	2 kHz to 100 kHz 2 kHz to 52 kHz
Detection range <sup>1</sup>	0.5 to > 50 meters (1.6 to > 164 feet)	0.5 to > 70 meters (1.6 to > 230 feet)	0.5 to > 120 meters (1.6 to > 393 feet)
Field of view (FOV)	63°± 5°		
Nominal frame rate	25 FPS		
<b>Built-in digital camera (visible light)</b>			
Field of view (FOV)	63°± 5°		
Focus	Fixed lens		
Zoom	No zoom	3 x digital zoom	
Resolution	0.3 MP	5.0 MP	
<b>Display</b>			
Size	7" LCD with backlight, sunlight readable		
Resolution	1280 x 800 (1,024,000 pixels)		
Touchscreen	Capacitive		
Acoustic image	SoundMap™ image		
<b>Image storage</b>			
Storage capacity	20 GB (> 5,000 pictures / > 999 videos)	32 GB (> 8,000 pictures / > 1,600 videos)	
Image format	Blended visual and SoundMap™ .JPG or .PNG		
Video format	Blended visual and SoundMap™ .MP4		
Video length	Up to 5 minutes		
Digital export	USB-C for data transfer		
<b>Acoustic measurements</b>			
Measurement range (typical)	15.4 to 115.2 dB SPL (± 1 dB SPL 2 kHz) 5.6 to 102.5 dB SPL (± 2 dB SPL 19 kHz) 28.4 to 131.1 dB SPL (± 1 dB SPL 35 kHz) 41.8 to 133.1 dB SPL (± 3 dB SPL 52 kHz)	15.4 to 115.2 dB SPL (± 1 dB SPL 2 kHz) 5.6 to 102.5 dB SPL (± 2 dB SPL 19 kHz) 28.4 to 131.1 dB SPL (± 1 dB SPL 35 kHz) 41.8 to 133.1 dB SPL (± 3 dB SPL 52 kHz)	12.1 to 114.6 dB SPL (± 1 dB SPL 2 kHz) 4.4 to 101.2 dB SPL (± 2 dB SPL 19 kHz) 12.8 to 119.2 dB SPL (± 1 dB SPL 35 kHz) 19.8 to 116.1 dB SPL (± 3 dB SPL 52 kHz) 41.4 to 129.0 dB SPL (± 1 dB SPL 80 kHz) 54.4 to 135.5 dB SPL (± 1 dB SPL 100 kHz)
<b>Classification and quantification</b>			
LeakQ™	Leak size scale (1-10)	Leak size scale, Leak rate, and Leak cost estimation	
PDQ Mode™	-	-	Partial discharge type classification
MecQ™	-	-	Mechanical anomaly detection
Auto max/min dB gain	Auto	Auto or manual, user selectable	
Frequency band selection	User selectable through user-made presets or manual entry		
<b>Battery</b>			
Battery	Rechargeable and field replaceable Li-ion battery		
Battery life	6 hours		
Battery charging time	3 hours	4 hours	
Battery charging system	External (Bay charger)	Internal (USB-C)	

<sup>1</sup> Depending on ambient conditions

Key Features	ii500	ii905	ii915
<b>Software</b>			
Ease of use	Intuitive user interface		
Acoustics: Show dB scale	On/Off		
Acoustics: Min/Max dB	Manual/Auto		
Acoustics: Profiles	-	Preset capture profiles	
Acoustics: High frequency	-		Yes
Acoustics: Multiple sources	Single source	Show single or multiple sources	
Palette: Colors	3: Grayscale, Ironbow, and Blue-Red		
Palette: Overly transparency	Yes: 1-100 %		
Grayscale mode	Yes		
Centerpoint markers	On/Off		
Trend graphs	Frequency and dB scale		
Spotmarkers	dB level reading at center point of image		
Leak values	LeakQ™ scale (1-10)	Leak costs, Leak volume, LeakQ™ scale (1-10)	
Master admin menu	-	Yes	
Annotation	Asset name; Asset ID; Asset type; Leak type; Gas type; Pressure		
Photo notes	Up to 4 photos notes for reference		
Asset inspection status	-	'As left', 'As found', 'Undetermined'	
Asset ID	Text input and automatic QR code based asset ID identification		
Actions annotation	-	Action requirements, Action priority level, Action notes	
Other	-	Operating conditions, Weather notes	
<b>General specifications</b>			
Tripod holder / connector	-	Yes: 1/4"-20	
USB	1 x USB-C	2 x USB-C	
Wireless	-	Wi-Fi	
Operating Temperature	-10 to 45 °C (14 to 113 °F)	-10 to 45 °C (14 to 113 °F)	-10 to 40 °C (14 to 104 °F)
Storage Temperature	-20 to 70 °C (-4 to 158 °F) without batteries installed		
Relative humidity	10 to 95 % non-condensing		
Size (H x W x L)	186 mm x 322 mm x 68 mm (7.3 inches x 12.7 inches x 2.7 inches)		
Weight (battery included)	2.1 kg (4.6 pounds)	2.0 kg (4.4 pounds)	
Ingress Protection (IP)	IP40		
Warranty	2 year		
Fluke Premium Care	Premium Care Standard <sup>2</sup>		
Self-diagnostic notification	Array-health test to identify when microphone array needs attention		
Supported languages	Dutch, English, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Simplified Chinese, Spanish, Swedish, Traditional Chinese		
RoHS compliant	Yes		
<b>Safety</b>			
General safety	IEC 61010-1: Pollution degree 2		
Electromagnetic Compatibility (EMC) International	IEC 61326-1: Portable Electromagnetic Environment, CISPR 11: Group 1, Class A	IEC 61326-1: Industry Electromagnetic Environment, CISPR 11: Group 1, Class A	
Korea (KCC)	Class A Equipment (Industrial Broadcasting and Communication)		
USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103	47 CFR 15 subpart C	

# Fluke Built, Fluke Protected

FLUKE®

## Reduce unplanned expenses and get the most out of your tools with Fluke Premium Care

When you invest in the best equipment in the industry, you want your money to go as far as possible. Fluke Premium Care provides coverage above and beyond your tool's original product warranty, so you don't need to worry about unexpected downtime caused by damaged test equipment, accessories, or tools in need of calibration or repair.

**Fluke Premium Care Standard** is available with one-year or three-year plan options so you can choose the plan that is right for you.



	Standard Warranty	Premium Care Standard
Repair manufacturing defects	✓	✓
Accidental damage and repair		✓
Replacement of damaged accessories		✓
Annual calibration or performance check		✓
Expedited calibration and repair		✓
Priority tech support		✓
Software updates		✓
Expedited shipping		✓

## PremiumCare

Uptime Protection by **FLUKE**



### Repair manufacturing defects

Ensuring that your equipment functions as intended maintains accuracy and reliability, thereby reducing downtime and ensuring the longevity of your Fluke product.



### Accidental damage and repair

Avoid costly repairs and rest easy knowing your test tool is covered in the event it gets damaged.



### Replacement of damaged accessories

Accessories that originally shipped with your unit, like batteries, power adapters, probes and cables, and have been qualified as defective by our technicians will be replaced, free of charge.



### Annual calibration or performance check

Ensure your test tool is providing accurate results and adheres to the recommended maintenance schedule by leaving it in the hands of our experts.

### Expedited calibration and repair

Your calibration or repair will be expedited with priority next-on-bench service and shipping so you can get back to your work faster.



### Expedited shipping

Accelerates the shipping process, reducing the time your equipment spends in transit, while minimizing the overall turnaround time to ensure that your Fluke product is back in your hands and operational as quickly as possible.



### Software updates

Maintain peak performance with firmware updates that ensure your tool remains reliable and up to date, automatically applied during equipment calibration.



### Priority tech support

Ensures prompt assistance and resolution of technical issues, minimizing downtime by quickly addressing any problems or concerns with your Fluke equipment.



## Ordering information

FLK-ii500 Acoustic Imager

FLK-ii905 Acoustic Imager

FLK-ii915 Acoustic Imager

### Included

Acoustic Imager; Power supply\*; Lithium-ion smart battery pack;  
USB-C cable; Rugged hard carrying case; Array sensor cover;  
Adjustable hand strap, and adjustable neck strap.

\* ii500 includes a battery charging bay.

Visit **fluke.com** to get complete details on these products  
or ask your local Fluke sales representative.

**Fluke.** Keeping your world up and running.™

©2024 Fluke Corporation.  
Specifications subject to change without notice.  
240545-en

Modification of this document is not permitted  
without written permission from Fluke Corporation.