



## ACCURACY—PRESSURE MEASUREMENT

0 to 110% of Range:  $\pm(0.05\% \text{ of Reading} + \text{Floor Term})$

Floor Term: **0.005% of FS or display resolution, whichever is greater**

Vacuum:  $\pm(0.25\% \text{ of Reading} + \text{Vacuum Floor Term})$

Vacuum Floor Term: **0.004 psi for 16 and 36 psi  
0.01 psi for 300 psi**

*Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.*

*All models indicate vacuum, but vacuum specification applies to 16 psi, 36 psi, and 300 psi models only.*

*Not recommended for continuous use below -14.5 psi. Refer to [XP2i-DP data sheet](#) for gauges that are intended for continuous high vacuum use.*

## ACCURACY—MILLIAMPERES

Accuracy:  $\pm(0.025\% \text{ of Reading} + 0.001 \text{ mA})$

Range: **0 to 55 mA**

Resolution: **0.001 mA**

Connection: **4 mm jacks, 19 mm (0.75") spacing**

*Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.*

*mA can be displayed as a percentage, where 0 to 100% corresponds to either 4 to 20 mA or 10 to 50 mA.*

*Jacks are compatible with safety sheathed banana plugs.*

## OPERATING TEMPERATURE

Temperature Range: **0 to 50° C (32 to 122° F)**

*Non-condensing. No change in accuracy over operating temperature range. Gauge must be zeroed to achieve rated specification.*

## DISPLAY


Screen: **2 lines of up to 6 digits,  
5 mm (0.2") high**

Display Rate: **2 readings/second (Adjustable to  
1, 3, or 3.7 readings/second)**

*LCD readable in sunlight.*

*Changes to reading rate requires software: ConfigM30 is a free download from [ametekcalibration.com](http://ametekcalibration.com).*

## 30 Series Calibrator psi



### PRESSURE PORT VOLUMETRIC DATA:

LP distance to diaphragm (A to B): 22.4 (0.88")

LP volume: 2 ml (0.13 cubic inches)

HP distance to diaphragm (A to B): 17.8 (0.70")

HP volume: 1 ml (0.06 cubic inches)

## POWER

The 30 Series is Intrinsically Safe only if powered by one of the following battery types.

ATEX/IECEx:	Approved Battery Type	Ta=	Marking
	Duracell Alkaline 9V, MN 1604	0 to 50° C	Ex ia IIC T4 Gb
	Energizer Alkaline 9V, 522		
	Energizer Lithium 9V, L522		
	Varta High Energy Alkaline 9V, 4922	0 to 45° C	

CSA:	Approved Battery Type	Marking
	Duracell Alkaline 9V, MN 1604	Class I, Division 1, A, B, C, D T4
	Energizer Alkaline 9V, 522	
	Energizer Lithium 9V, L522	
	Varta High Energy Alkaline 9V, 4922	Class I, Division 1, A, B, C, D T3C

1 x 9V: **90 hours, typical**

Uses one alkaline 9V battery. Use of USB interface reduces operating time.

For hazardous location product warnings, refer to the operation manual.

## DATA/COMMUNICATION

Digital Interface: **micro-USB**

Free Labview drivers available online.

For hazardous location product warnings, refer to the operation manual.

## ENCLOSURE

Model 31 ≤300 psi: **342 g (12.0 oz)**

Weight includes batteries.

\* Model 31 ≤300 psi: **428 g (15.0 oz)**

\*SPSS optional manifold.

Model 31 ≥1500 psi: **360 g (13.0 oz)**

Model 33: **400 g (14.0 oz)**

\* Model 33: **485 g (17.0 oz)**

Housing: **Extruded aluminum**

Keypad and Labels: **UV resistant polyester**

## CERTIFICATIONS



**II 2G Ex ia IIC T4**  
**FTZU 06 ATEX 0010X**



**II 2G Ex ia IIC T4 Gb**  
**IECEx FTZU 10.0018X**



Exia Intrinsically Safe and Non-incendive for Hazardous Locations: Class I, Division 1, Groups A, B, C and D, Temperature Code T4 or T3C. For hazardous location product warnings, refer to the operation manual.



30 Series complies with the Electromagnetic Compatibility and the Pressure Equipment Directives.



30 Series complies with the Australian Radiocommunications (Electromagnetic Compatibility) Standard 2008



30 Series is approved for use as a portable test instrument for Marine use and complies with Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Offshore Standards.

#### SENSOR $\geq$ 1500 psi

Wetted Materials: **316 stainless steel** *All welded with a permanently filled diaphragm seal.*  
Diaphragm Seal Fluid: **Silicone Oil**  
Connection: **Bottom, 1/8" female NPT**

#### SENSOR $\leq$ 300 psi

Wetted Materials: **316 stainless steel, Viton® (o-ring)** *Viton o-ring is internal.*  
**Anodized aluminum penetrated with PTFE (polytetrafluoroethylene)** *All welded with a permanently filled diaphragm seal.*  
Diaphragm Seal Fluid: **Silicone Oil**  
Connection: **Bottom, 1/8" female NPT**

#### STORAGE TEMPERATURE

Temperature Range: **-20 to 70° C (-4 to 158° F)** *Batteries should be removed if stored for more than one month.*

#### SPECIAL FEATURES

The following requires the use of [ConfigM30](#) software

User Defined Unit: **Allows the user to define and display any pressure units not included, or to use the gauge to display force, level, or other pressure related parameters. Reduce or increase displayed resolution.**

Remove: **Unwanted pressure units from Units button.**

Password Protect: **Changes to configuration or userspan calibration factor(s).**

Save: **Configuration to a file.**

Copy: **Configuration to other calibrators.**

#### STANDARD DELIVERY

- 30 Series Calibrator
- CD Manual
- ISO 17025 Accredited Calibration Certificate, NIST Traceable

#### ACCESSORIES

**Magnetic Hanging Strap** [P/N 5203](#)

**Test Lead Kit** [P/N 1351](#)

**USB A to Micro USB Cable** [P/N 4431](#)

**Waterproof Carrying Case** [P/N 2888](#)

#### COMPLEMENTARY PRODUCTS

**Crystal Engineering offers a wide range of products that work with the 30 Series:**

- [Fittings that connect without tools, safely and without leaks](#)
- [Lightweight, super flexible high pressure hoses](#)
- [Pneumatic hand pumps](#)
- [Hydraulic hand pumps](#)
- [Portable pressure comparators](#)
- [Software, for the quickest way to calibrate pressure transmitters and gauges](#)

Viton is a registered trademark of DuPont Performance Elastomers.

## RANGE & RESOLUTION TABLE

P/N	Range (psi)	Over-pressure	Display Resolution									
			psi	in H <sub>2</sub> O	in Hg	mm Hg	mm H <sub>2</sub> O	cm H <sub>2</sub> O	kg/cm <sup>2</sup>	bar	mbar	kPa
16	16	6.5 x	0.001	0.01	0.001	0.01	1		0.0001		0.1	0.01
36	36	3.0 x	0.001	0.01	0.001	0.01	1		0.0001		0.1	0.01
300	300	2.0 x	0.01	0.1	0.01	0.1		1	0.001	0.001		0.1
1500	1500	2.0 x	0.1						0.01	0.01		1
3000	3000	1.5 x	0.1						0.01	0.01		1
5000	5000	1.5 x	0.1						0.01	0.01		1

Model 31 calibrators are not available in this range.

## DUAL PRESSURE SENSORS

Model 33 calibrators have dual pressure sensors. This chart shows all of the available sensor combinations. ■

First Pressure Ranges	Second Pressure Ranges			
	300 psi	1500 psi	3000 psi	5000 psi
16 psi	■	■	■	■
36 psi	■	■	■	■

## ORDERING INFORMATION

Intrinsic Safety	Model	1st Pressure Range P/N	2nd Pressure Range P/N	Pressure Unit	Pressure Manifold
IS				PSI	
	Single Sensor...31				Standard.....(omit)
	Dual Sensor...33				Stainless Steel...SPSS

### SAMPLE PART NUMBERS

IS31-36PSI ..... Calibrator with one sensor (36 psi).  
 IS33-16/1500PSI-SPSS ..... Calibrator with two sensors (16 psi and 1500 psi) with two stainless steel manifolds.  
 IS33-36/3000PSI-SPSS-HOX-W ..... Calibrator with two sensors (36 psi and 3000 psi) and two stainless steel manifolds with a System H pump system and a waterproof carrying case.

### Ordering a Pump System Only

Any pump system, carrying case, and connection fittings for a 30 Series calibrator may be ordered separately from the calibrator. Enter IS30-NONE followed by the Pump System part number and the Carrying Case option code.

### SAMPLE PART NUMBER

IS30-NONE-HOX-W ..... System H pump system with a waterproof carrying case.

Pump System*	Carrying Case~
No Pump.... (omit)	
System A.... -AXX	Aluminum ... (omit)
System A.... -AHX	Waterproof..... -W
System B.... -BXX	
System B.... -BHX	
System C.... -CXX	
System C.... -CHX	
System D.... -DOX	
System D.... -DWX	
System E.... -EOX	
System F.... -FOV	
System F.... -FWV	
System G.... -GOX	
System G.... -GWX	
System H.... -HOX	
















~ The Waterproof Case is an option for Systems A, B, and C only.  
 The Waterproof Case is the only option for Systems G and H.

AMETEK offers a variety of solutions for pressure generation and measurement. Our line of products for pressure generation includes everything from small pneumatic hand pumps to a precision, hydraulic pressure comparator capable of generating up to 15 000 psi / 1000 bar / 100 MPa.

All of our pumps may be ordered as part of a Pump System, complete with a 30 Series and delivered in a sturdy carrying case with custom insert.

\* Refer to the following page for a more detailed description of each pump system.

**PUMP SYSTEMS OVERVIEW**

Pump System	Part Number	Pressure Range	Pneumatic	Hydraulic	Hand Pump	Bench Top	Included Pump	Case Options	
								Aluminum	Waterproof (Pelican Case)
System A	AXX	0 to 30psi / 2 bar	■		■		 T-960-CPF	■	■
	AHX	0 to 580 psi / 40 bar	■		■		 T-970-CPF	■	■
System B	BXX	-25 inHg to 30 psi / -0.85 to 2 bar	■		■		 T-965-CPF	■	■
	BHX	-27 inHg to 580 psi / -0.91 to 40 bar	■		■		 T-975-CPF	■	■
System C	CXX	0 to 3000 psi / 200 bar		■ (Oil)	■		 T-620-CPF	■	■
	CHX	0 to 5000 psi / 350 bar		■ (Oil)	■		 T-620H-CPF	■	■
System D	DOX	0 to 5000 psi / 350 bar		■ (Oil)		■	 P-018-CPF	■	
	DWX	0 to 5000 psi / 350 bar		■ (Water)		■	 P-014-CPF	■	
System E	EOX	0 to 10 000 psi / 700 bar		■ (Oil)		■	 T-1-CPF	■	
System F	FOV	0 to 15 000 psi / 1000 bar		■ (Oil)		■	 GaugeCalHP	■	■
	FWV	0 to 15 000 psi / 1000 bar		■ (Water)		■	 GaugeCalHP	■	■
System G	GOX	0 to 15 000 psi / 1000 bar		■ (Oil)		■	 GaugeCalHP		■
	GWX	0 to 15 000 psi / 1000 bar		■ (Water)		■	 GaugeCalHP		■
System H	HOX	-27 inHg to 580 psi / -0.91 to 40 bar	■		■		 T-975-CPF		■
		0 to 5000 psi / 350 bar		■ (Oil)	■		 T-620H-CPF		■