### 8" CHART RECORDER

# Model: KT8-31R



8" (203mm) chart recorders offer the largest resolution out of any chart recorders. All chart recorders feature a large 8" chart and user-selectable recording time-frames and ranges. These units are compatible with Dickson's Replaceable Sensors™, making calibrating your chart recorder easier than ever.

### **FEATURES:**

- Display
- Audible Alarms
- Relays
- Dual K-Thermocouple Replaceable Sensor™

## REPLACEABLE SENSORTM SPECIFICATIONS:

#### **Temperature Accuracy**

 $\pm 1.8^{\circ} F$  from -300°F to 122°F ( $\pm 1^{\circ} C$  from -185°C to 50°C)  $\pm 3.8^{\circ} F$  ( $\pm 2.1^{\circ} C$ ) remaining range

#### **Temperature Range**

-300°F to 2000°F (-185°C to 1093°C)

Alarm Type	Audio/Visual/Relay on High/Low Limits
Ambient Operating RH Conditions	0-95% RH non-condensing
Ambient Operating Temperature Conditions	32°F to 120°F (0°C to 50°C)
Battery Backup	(4) C Batteries
Battery Life	1 Month (Avg)
Calibration Options	N100, N300, N400
Channels	CH1: Temperature CH 2: Temperature
Chart Rotation Speed	24 Hour, 7 Day
Dimensions LxWxH	9 3/8"x2 3/4"x10 1/8"
Display Dimensions	5 1/8" x 1"
Display Type	LCD
Enclosure	Rugged Black ABS Case, Polycarbonate Door, Aluminum Dial
IP Rating	IP20
Included Accessories	AC Adapter, Red Pen, Blue Pen, (4) C Batteries, Quick Start Guide and Replaceable Sensor™ *Charts sold separately
Mounting Options	Free Standing or Wall Mount (With Keyhole)
Power Cord	6 ft
Power Source	120 to 240 VAC, 12 VDC (INTL fittings available); AC Adapter
Power Status Indicator	LED Indicator
Unit Weight	2.45lbs without batteries
Warranty	12-Month Limited
Replaceable Sensor SKU	RS031

Your Proven Partner for Environmental Monitoring



