

8" (203mm) Temperature Chart Recorder



Specifications

Ambient Operating RH Conditions : 0-95% RH non-condensing (Recorder Only) **Ambient Operating Temperature Conditions:** 32.0 to 122.0F (0.0 to 50.0C)

Approvals: CE

Calibration Options: N100, N300, N400

Channels: CH1: Temperature

Chart Rotation Speed: 24 Hour, 7 Day

Dimensions: 3.1 x 9.2 x 9.2in

Enclosure: Rugged Black ABS Case, Poly-carbonate Door, Aluminum Dial

IP Rating: 20

Included Accessories: Red Pen, Four AA Batteries, Quick Start Guide and 4' Bead-Wire Probe. *Charts sold

separately

Keypad Functions: Power On/Off, Pen Home **Mounting Options:** Free Standing or Wall Mounted **Power Source:** Four AA Batteries (User Replaceable)

Power Status Indicator: LED **Remote Sensor Length:** 4

Remote Sensor Type: 1 K-Thermocouple Probe, Replaceable Sensor

Response Time: 30 Seconds to 63% of Full Scale

Temperature Accuracy: +/-1.8F from -22.0 to 122.0F 3.8F (+/-1.0C from -30.0 to 50.0C 2.1C)

Temperature Range: -50.0 to 50.0F/C; -20.0 to 20.0F/C; 0.0 to 100.0F/C; 0.0 to 150.0F/C; 0.0 to 250.0F/C; 0.0 to

500.0F/C; 0.0 to 1000.0F/C; 0.0 to 2000.0F; 50.0 to 150.0F/C

Temperature Sensor: Remote Probe

Unit Weight: 9 lbs

Units/Pkg: 1

Warranty: 12-Month Limited





Calibrations

N100: 1-Point NIST Traceable Calibration **N300:** 3-Point NIST Traceable Calibration

N400: 3-Point Ultima NIST A2LA Accredited Calibration

Accessories



A868 - Sensor Dust Filter Sensor Dust Filter - prolong the life of your sensor.



R400 - Replaceable Sensor Single K-TC Replaceable Temperature Sensor



A062 - AC Adapter Extension Cable 10' 10' Power Extension for R157 AC Adapter



R066 - Universal Plug Kit for Data Loggers International Plug Kit for Data Loggers



Accessories



R180 - Replacement AC Adapter AC Adapter for TSB/TWE/TWP Loggers and the KT8/KT6 series.



R013 - Temperature Probe Replacement Bead Wire Temperature Probe



A203 - Temperature Probe 6" (15cm) High Temperature Immersion Probe



A340 - Glycol BottleBottle of Glycol Solution w/ Septum Close



D605 - Piercing Probe 4" (10cm) Thermocouple Handled Piercing Probe



Accessories



D611 - Shielded Immersion Probe 15' (4.5m) Shielded Thermocouple with 4" (10cm) stainless steel tip



D617 - Probe Extension K-Thermocouple 10' (3m) Extension Cable



A202 - Thermocouple Extension K-Thermocouple 100' (30m) Extension Cable