



## Digital Multimeter TRMS/Low Impedance, 1000V

NO IMAGE  
AVAILABLE

Klein Tools MM700 Multimeter is an automatically ranging true root mean squared (TRMS) digital multimeter that measures AC/DC voltage, AC/DC current, and resistance. It can also measure temperature, capacitance, frequency, duty-cycle, diodes and continuity. Klein Tools' Test and Measurement product line was exclusively designed from the ground up by electricians for electricians. Years of field research, combined with extensive input from electricians across America, inspired the development of meters and electrical testers loaded with innovative, time-saving features.

### Specifications

|                           |                                                                         |                            |                                                                                                                                                               |
|---------------------------|-------------------------------------------------------------------------|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Batteries:</b>         | 2 x AAA                                                                 | <b>Drop Protection:</b>    | 6.6' (2 m)                                                                                                                                                    |
| <b>Display:</b>           | 4000 Count LCD                                                          | <b>Functions:</b>          | Measures up to 1000V AC/DC voltage, 10A AC/DC current and 40M $\Omega$ resistance plus temperature, capacitance, frequency, duty-cycle, diodes and continuity |
| <b>Voltage:</b>           | 1000V AC; 1000 V DC                                                     | <b>Frequency:</b>          | 1Hz - 500 KHz                                                                                                                                                 |
| <b>Current:</b>           | 10A AC; 10A DC                                                          | <b>Capacitance:</b>        | 4000 $\mu$ F                                                                                                                                                  |
| <b>Ohms (Resistance):</b> | 40M $\Omega$                                                            | <b>Ingress Protection:</b> | IP42                                                                                                                                                          |
| <b>Standard:</b>          | CAT IV 600V                                                             | <b>Temperature Range:</b>  | 0° - 1500°F (-18° - 816°C)                                                                                                                                    |
| <b>Included:</b>          | Carrying Case, Test Leads, Thermocouple, Batteries, and Alligator Clips | <b>Overall Length:</b>     | 7" (17.8 cm)                                                                                                                                                  |
| <b>Overall Height:</b>    | 2.09" (5.3 cm)                                                          | <b>Overall Width:</b>      | 3.55" (9 cm)                                                                                                                                                  |
| <b>Weight:</b>            | 14.4 oz (408 g)                                                         |                            |                                                                                                                                                               |