

SHIMPO INSTRUMENTS

The Shimpo Series ST-1000 is a Stroboscope-Tachometer with LED flash technology. This velocity analyzing and measuring device is ideal for rotational machine inspection. The stroboscope is capable of flashing the light in a synchronous frequency to the operating machinery, creating the illusion of viewing stopped or slowed images. Utilizing this phenomenon of slowing or stopping the motion with the adjusted rate of the ST-1000's flashing light, machine parts and processes may be inspected for defects. Plus, the rotational speed of the machinery and systems may be recorded for further performance analysis.

The ST-1000 is adjustable in either coarse or fine step flash-rate tuning. The backlit display shows the current flash rate, 10 user-stored pre-set flash rates, as well as a low battery warning. The backlit feature can be switched off to save battery life if desired. The ergonomic, hand held device is made of sturdy ABS plastic and comes with batteries and protective carrying case. The LED technology extends operation due to the low energy requirement of the light diodes compared with xenon stroboscopes. Typical applications for using the ST-1000 is to inspect rotors, meshing gears, vibration diagnostic equipment, textile equipment, printing production lines, power tools, speaker acoustical analysis, fan balancing and many more.

Measuring Quality

Series ST-1000 LED Stroboscope Tachometer



Easy Operation Control



Flash Rate
Storage Button



READ

Power Switch

UP

Flash Rate Value increase button

DOWN

Flash Rate Value decrease button

FINE
ADJUST

Coarse/Fine tuning button



Flash Rate Storage Button - 10 user defined flash rates for later retrieval

A Nidec Group Company

SHIMPO

NIDEC SHIMPO AMERICA CORPORATION

1.800.561.8187

www.itm.com

information@itm.com

ST-1000 Specifications

Range	60-40,000 Flash Rate Per Minute (RPM)
Accuracy	+/-0.05% FS
Lux Rating	650 Lux @ 3000 RPM & 3.9 in (10 cm); 350 Lux @ 3000 RPM & 7.9 in (20 cm); 185 Lux @ 3000 RPM & 11.8 in (30 cm)
Display	5 digits with backlight 40000 maximum reading
Resolution	<1000 RPM: 0.1 RPM; >1000 RPM: 1 RPM
Tuning	<1000 RPM: Coarse=10 RPM increments; Fine= 0.1 RPM increments. >1000 RPM: Coarse=100 RPM increments; Fine= 1 RPM increments
Rate Storage	10 stored user-defined flash rates. Factory Defaults: 4000, 8000, 12000, 16000, 20000, 24000, 28000, 32000, 36000, 40000.
Power Supply	4 AA batteries
Housing	ABS Plastic
Dimensions	7.7 x 2.9 x 1.5" (195 x 73 x 38 mm)
Product Weight	Approx. 7 oz. (200 g)
Package Weight	Approx. 1.5 lb (680.4 g)
Certification	CE
Included Accessories	Protective carrying case, 4 AA batteries
Warranty	1 year

Ordering Details

ST-1000	LED Stroboscope Tachometer with Included Protective Carrying Case
----------------	---



ST-1000 Checking Fan Speed and Balance



ST-1000 Acoustical Speaker Analysis