


EXTERNAL PROBES AND SENSORS


ST100 range

The LogTag® ST100 probe range is distinguished from other remote temperature probe types by the blue sleeve blue body at the plug end of the probe cable. All materials at probe end of the cable are FDA food rated, including the cable (except ST100B), and terminated with a high quality gold plated MCX connector & industrial strength PTFE coaxial cable.




ST100H - Handled Long Tipped Probe

Part #:	ST100H-15: 1.5m (4'11") ST100H-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316




ST100J - Short Round Tip Probe

Part #:	ST100J-15: 1.5m (4'11") ST100J-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316



ST100K - Medium Round Tip Probe

Part #:	ST100K-15: 1.5m (4'11") ST100K-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316



ST100L - Long Round Tip Probe


Part #:	ST100L-15: 1.5m (4'11") ST100L-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316

LogTag Recorders

information@itm.com


www.itm.com

1.800.561.8187




ST100T - Long Tipped Sensor Probe

Part #:	ST100T-15: 1.5m (4'11") ST100T-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316




ST100S - Short Round Tip Sensor Probe

Part #:	ST100S-15: 1.5m (4'11") ST100S-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316



ST100B - Untipped Bare Sensor

Part #:	ST100B-15: 1.5m (4'11") ST100B-30: 3.0m (9'10")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers




ST100KF - External Temperature Probe Flat Cable

Part #:	ST100KF-05: 0.5m (1'6")
Compatible Loggers:	TREX loggers TRED30 loggers UTRED & UTRED30 loggers
Stainless Probe Type:	316


ST10 range (Ultra-Low Temperature)

The LogTag® ST10 probe range is distinguished from other remote temperature probe types by the green sleeve green body at the plug end of the probe cable and is suitable for the TREL/UTREL models. The probe is terminated with a high quality gold plated MCX connector & industrial strength PTFE coaxial cable.



ST10S - Short Round Tip Probe

Part #:	ST10S-05: 0.5m (1'6") ST10S-15: 1.5m (4'11") ST10S-30: 3.0m (9'10")
Compatible Loggers:	TREL & TREL30 loggers UTREL & UTREL30 loggers
Stainless Probe Type:	316




ST10M - Medium Round Tip Probe

Part #:	ST10M-15: 1.5m (4'11") ST10M-30: 3.0m (9'10")
Compatible Loggers:	TREL & TREL30 loggers UTREL & UTREL30 loggers
Stainless Probe Type:	316

STX-50

5 meter (~16' 5") extension cable for extending ST10 or ST100 external temperature sensors. The socket end of the cable (which accepts the ST100 or ST10 sensor plug) is fitted with a flexible sleeve that when the ST sensor's plug is in place will protect the mated connection to IP61.



Part #:	STX-50
Environmental:	Logger to extension connection rating: IP61 (when logger vertically mounted or hung) Extension to probe connection rating: IP61, -46°C (-50.8°F) ~ +74 °C (165.2°F)
Compatibility:	For extending ST100 and ST10 external temperature sensors* *only 1 extension per logger

STX-50 - External Sensor Extension cable