

FLIR T420 & T440

High Performance Infrared Camera With on-board Visual Camera, Thermal Fusion, Touch Screen, Wi-Fi Connectivity, & Interchangeable Lens, Plus MSX™ Image Enhancement & FOV Match

Get maximum flexibility and efficiency out of 320 x 240 thermal imaging from our new T400 line:

Superior Thermal Imaging – Sharp thermal resolution at 76,800 pixels for solid accuracy from farther away

New! MSX™ Enhancement – Multi-Spectral Dynamic Imaging adds visible spectrum definition to IR images in real time for extraordinary thermal detail that instantly highlights and orients problem locations (T440 only)

New! Field of View (FOV) Match – Now you have the option to automatically match the visible camera field of view to the IR FOV for better documentation

Wi-Fi Connectivity – Send images and data to smart phones and tablets (i.e. iPhone®, iPad®, iPod touch®, or Android™) to share images and critical information quickly using FLIR Tools Mobile app

Accurate Temperature Measurements – Accuracy calibrated within +/– 2°C or +/– 2% of reading

High Temperature Range – measuring up to 2192°F (1200°C) targeting electrical and industrial applications (T440 model)

Scalable P-i-P and Thermal Fusion – Blend thermal with visible light images on-screen; includes picture-in-picture window sizing

Multiple Measurements – Add up to 5 box areas and 5 moveable spots using the touchscreen to gather more detailed information

METERLiNK® – Wirelessly transmit vital diagnostic data from clamp and moisture meters directly to the camera for annotating thermal images to further support findings and decisions

Annotation – Add voice comments via Bluetooth headset and text notes from the touchscreen keypad; New! T440 has image sketch feature to draw circles and pointers on IR/Visual stored images

InstantReport – Create PDF document directly from the camera

Includes – SD Memory Card, 100-260V AC adaptor/charger, two Li-Ion rechargeable batteries, 2-bay battery charger, power supply (with multi-plugs), FLIR Tools software, USB cable, video cable, sun shield, Bluetooth® headset, lens cap, neckstrap, and hard case



Wi-Fi Connectivity



Original IR Image on the Left and with MSX™ Enhancement on the Right image [available on T440 model]



Built-in 3.1MP Digital Camera, LED Lamp, Laser Pointer, Fine Focus Adjust, and Auto focus & Image Capture Button. 120° Rotating Lens with 8X Continuous Zoom



Thermal Fusion is an Infrared image shown above, below or within temperature interval blended onto a digital image



Wireless METERLiNK® Communication via Bluetooth®



Applications



Utility Market — Utilities worldwide use infrared cameras to locate problems or to detect hot spots and other problems before they turn into costly failures and production downtime or dangerous electrical fires.

Electrical Inspections — With FLIR thermal imaging cameras electrical contractors can scan electrical cabinets/panels and components for a non-contact view of conditions.

Imaging Specifications

| FEATURES | FLIR T420 | FLIR T440 |
|---|--|---|
| Temperature range | -4°F to 1202°F (-20°C to 650°C) | -4°F to 2192°F (-20°C to 1200°C) |
| Zoom | 4X Continuous | 8X Continuous |
| LCD Image Sketch | — | Draw on stored images right on touchscreen |
| Multi-Spectral Dynamic Imaging (MSX) | — | IR image with enhanced detail presentation |
| Measurement Presets | — | Presets for standard measurements |
| Profile Measurement Analysis | — | Shows a live graph of temperatures across a line on the image |
| COMMON FEATURES | | |
| Frame Rate | 60Hz | |
| Field of view/Minimum focus distance/FOV Match | 25° x 19° / 1.31ft (0.4m) / Field of View Match where Digital Image FOV adapts to the IR lens | |
| Focus | Manual/Automatic | |
| Thermal sensitivity (N.E.T.D) | <0.045°C at 30°C | |
| Detector Type - Focal plane array (FPA) uncooled microbolometer | 320 x 240 pixels | |
| Spectral range | 7.5 to 13µm | |
| Display | Built-in touch-screen 3.5" color LCD | |
| Image modes | Thermal/Visual/Fusion/P-i-P and Thumbnail Gallery | |
| Image Storage | 1000 radiometric JPEG images (SD card memory) | |
| Image annotation | Voice (60 sec); text comments, Sketch, image markers on IR | |
| Periodic image storage | 7 seconds to 24 hours (IR) and 14 seconds to 24 hours (IR and visual) | |
| Lens | 25° (optional 6°, 15°, 45°, 90°, Close up 100, 50µm lenses available) | |
| Video Lamp | Bright LED lamp | |
| Laser Classification/Type | Class 2/Semiconductor AlGaInP Diode Laser: 1mW/635nm (red) | |
| Set-up controls | Mode selector, color palettes, configure info to be shown in image, local adaptation of units, language, date and time formats, and image gallery | |
| Measurement modes | 5 Spotmeters, 5 Box areas, Isotherm, Auto hot/cold spot, Delta T | |
| Measurement correction | Reflected ambient temperature & emissivity correction | |
| Video Recording in Camera and Video Streaming | Non-radiometric IR-video recording (MPEG-4 to memory card), Radiometric IR-video streaming (Full dynamic to PC using USB or Wi-Fi), and Non-radiometric IR-video streaming (MPEG-4 using Wi-Fi and uncompressed colorized video using USB) | |
| Instant Report | Create a Thermographic Inspection report directly in the camera | |
| Battery Type/operating time | Li-Ion/ >4 hours, Display shows battery status | |
| Charging system | In camera AC adapter/2 bay charging system | |
| Shock / Vibration | 25G, IEC 60068-2-29 / 2G, IEC 60068-2-6 | |
| Dimensions/Weight | 4.2x7.9x4.9" (106x201x125mm)/1.94lbs (0.88kg), including battery | |
| 2-5-10 Warranty | When the camera is registered within 60 days: 2 years on Parts/Labor for the Camera; 5 years of Coverage on Batteries; 10 years of Protection on the IR Detector | |

Ordering Information

62101-0101 FLIR T420 Thermal Imaging InfraRed Camera (320x240)
 62101-0301 FLIR T440 Thermal Imaging InfraRed Camera (320x240)

ACCESSORIES

1196398 Li-Ion Rechargeable Battery
 1910490 Cigarette Lighter Adapter Kit, 12VDC (1.2m cable)
 T197650 2-Bay Battery Charger including Power Supply (multi plugs)
 T911048 Camera Pouch Case
 T197717 FLIR Reporter Professional
 4114887 FLIR ThermaTrak™

CERTIFICATION TRAINING

ITC LEVEL I ITC Level I Certification Training per attendee



10-Year Detector Protection
 5-Year Battery
 2-Year Parts & Labor



PH: +1 877.239.8324 | FAX+1 603.324.7864 | www.extech.com/tseries

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery used for illustration purposes only. Specifications are subject to change without notice. ©2012 FLIR Systems, Inc. All rights reserved. 3300 (Rev. 04/12)

www.flir.com
 NASDAQ: FLIR