


YOUR DATA, ANYWHERE, ANYTIME



**LogTag**®


**UTREL30-WiFi**

30 Day WiFi Dual-Channel  
Low Temperature Logger

1.800.561.8187

www.**itm**.com

information@itm.com




The LogTag® UTREL30-WiFi temperature data logger automatically uploads real-time temperature data to your LogTag® Online cloud account via your existing wireless network.


It features a large, easy-to-read display, along with many familiar attributes known from the LogTag® family of data loggers.

These include non-volatile memory that holds up to 32,000 temperature readings, or 16,000 readings per channel. A statistical memory storing maximum and minimum readings and alarm durations for each of the last 30 days.

## Accessories




**2x AAA Batteries**  
Not Included




**USB Cable**  
Included



**AC Adapter<sup>^</sup>**  
Included



**Wall Mount**  
Not Included



**Buffer assembly**  
Not Included  
(Silica sand recommended for temperatures below -40°C)



**Smart Probe**  
Not Included (Recommended)



**External Probe<sup>\*\*</sup>**  
Not Included. (Required)

*Compatible probes below:*

<b>CP10</b> (Smart Probe)	75mm tip length, ø3.2mm
<b>ST10S</b>	22mm tip length, ø5mm (Not recommended for use with buffer)
<b>ST10M</b>	65mm tip length, ø5mm.
<b>STX50</b>	5 Meter extension cable for ST10/ST100 sensors.

*ST10S Probes are available with a 0.5m, 1.5m or 3m cable  
ST10M Probes are available with a 1.5m or 3m cable  
E.g. ST10M-15 for 1.5m or ST10M-30 for 3m cable*

<sup>^</sup>US and EU adapter only  
<sup>\*\*</sup>Hot swappable external sensor probes.

# Features



Real-time data automatically uploaded via Wi-Fi to the LogTag® Online cloud.




Download data via LogTag® Analyzer or as a PDF (no software required) when Wi-Fi is unavailable.



Configure Wi-Fi settings using LogTag® Mobile application and Bluetooth®.



Check and reset Min-Max temperature reading at any time.



Read current temperature and latest Min-Max temperature at a glance.




View alarm status for up to 30 days at a glance.



Receive an instant call, SMS or WhatsApp alert from your logger when it detects an excursion\* so you can act immediately.



Measure and store up to 16,000 readings for each channel – enough for 67 days at 6 minute logging.



Can be powered by 2x AAA batteries (user replaceable) if external power is lost.



Second battery backup via a coin cell to ensure no data is lost.



Auto-pause function suspends alarm & statistic processing when the external probe is unplugged.



Two socket external probe with auto channel swap function.

\*Voice call and SMS message alerts require LogTag® Online paid subscription.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by



# Applications



Vaccine & Pharmaceuticals



Industrial



Cold Storage



Clinic



Transportation



Refrigerated Containers

# Specifications

<b>Product Model</b>	UTREL30-WiFi.
<b>Sensor Measurement Range</b>	-90°C to +40°C (-130°F to +104°F).
<b>Operating Temperature Range</b>	-30°C to +60°C (-22°F to +140°F).
<b>Storage Temperature Range</b>	10°C to +40°C (32°F to +104°F).
<b>Rated Temperature Reading Resolution</b>	0.1°C (0.2°F) for measurements -80°C to 10°C (-112°F to 50°F) 0.2°C (0.4°F) for measurements 10°C to 20°C (50°F to 68°F) and -90°C to -80°C (-130°F to -112°F) 0.3°C (0.5°F) for measurements 20°C to 30°C (68°F to 86°F) 0.5°C (0.9°F) for measurements 30°C to 40°C (86°F to 104°F) LogTag® Analyzer currently displays to one decimal place of °C or °F. The native resolution is what is stored in the LogTag®.
<b>Rated Temperature Reading Accuracy</b>	Better than ±0.5°C for -20°C to +10°C (-4°F to 50°F) Better than ±0.7°C for -50°C to -20°C (-58°F to -4°F) and +10°C to +30°C (50°F to 86°F) Better than ±1°C for -80°C to -50°C (-112°F to -58°F) and +30°C to +40°C (86°F to 104°F) Better than ±1.8°C for -90°C to -80°C (-130°F to -112°F)
<b>Probe Connectivity</b>	Up to 2
<b>Probe Compatibility</b>	All ST100 precision thermistor external probes can be interchangeably connected to the UTREL30-WiFi. Please refer to the page for External Probes on the LogTag® North America website.
<b>Recording Capacity</b>	16,129 temperature readings. 67 days at 6 minute logging. Day summary statistics memory (for display on LCD): up to 30 days of Min/Max/duration and alarm trigger statistics.
<b>Sensor Reaction Time</b>	Typically less than 2 minutes(T90) in moving air (1m/s) for ST10S type.
<b>Sampling Interval</b>	Configurable from 30 seconds to 18 hours.
<b>Logging Start Options</b>	Push button start (with configurable start delay from 1 minute to 72 hours) or specific date & time.
<b>Download Time</b>	Typically with full memory (16,129 readings) in less than 10 seconds.
<b>Environmental</b>	IP51 (when vertically mounted or hung with USB dust-cap in place).
<b>Calibration</b>	Factory calibrated using NIST equivalent reference equipment. Calibration certificate available on request.
<b>Power Source</b>	5V via micro USB socket or, 2 x 1.5V AAA batteries. CR2032 LiMnO <sub>2</sub> coin cell (backup logging function only).
<b>Battery Life</b>	Device should normally be powered via USB. AAA batteries provide backup power for up to 2 months.
<b>Connection Interface</b>	USB 2.0 / Micro-USB plug.
<b>WiFi</b>	802.11 b/g/n
<b>Bluetooth®</b>	Bluetooth® V4.2 BR/EDR and Bluetooth LE®
<b>Size</b>	141mm(H) x 72mm(W) x 18mm(T).
<b>Weight</b>	158g with AAA batteries, (134g - excluding probe and AAA batteries).
<b>Case Material</b>	Polycarbonate

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by LogTag® North America Inc. is under license. Other trademarks and trade names are those of their respective owners.



# Connection Software

Real-time data automatically uploaded via WiFi to the LogTag® Online cloud.

