

MEETS SPECIFICATIONS OF



EN ISO:3059

SPECTROLINE®

## uVision™ 365 STANDARD SERIES



Also Available

IP Rated, Fanless LED UV-A Inspection Lamps

UV-365ES, UV-365EH, & UV-365MEH

- ▶ Compact, cost-effective handheld inspection lamps
- ▶ Available in two intensities to suit your specific needs: **standard-intensity** & **high-intensity**
- ▶ Can be used in forensics, specialty UV applications, and NDT/NDE
- ▶ Mobile AC/DC version available!

**IP65  
RATED**



**Dust Tight &  
Water Resistant**



**Fanless &  
Cool Running**



**Lightweight  
& Rugged**

**FOR FLUORESCENT INSPECTION  
IN ANY INDOOR / OUTDOOR  
ENVIRONMENT**

**3 UV-A LEDS**

For wide and even  
area of coverage

**WHITE LIGHT LED**

Allows for scanning  
surface flaws

**LONG-LASTING  
UV-A LENSES**

Reduce the rate of  
solarization

**EASY CONTROL**

Grip-mounted, three-way rocker  
switch (white light/off/UV)

**FANLESS DESIGN**

Maintains optimum lamp  
temperature using state-of-  
the-art heat sinks

**PISTOL GRIP**

Comfortable,  
balanced control



**CERTIFICATE OF  
LIGHT OUTPUT**  
included with lamp



1.800.561.8187

www.**itm**.com

information@itm.com

# uVision™ 365 UV-365 STANDARD SERIES

MODEL	NOMINAL STEADY-STATE UV-A (365 nm) INTENSITY at 15 in (38 cm) ①	VISIBLE LIGHT MEASUREMENT	UV-A COVERAGE AREA at 15 in (38 cm) at minimum 1,200 µW/cm²	AC/DC MOBILE VERSION
UV-365ES*	4,700 µW/cm²	< 1 foot-candle (11 lux)	6 in (15.24 cm) Diameter	
UV-365EH*	7,000 µW/cm²	< 1 foot-candle (11 lux)	7 in (17.78 cm) Diameter	
UV-365MEH*	7,000 µW/cm²	< 1 foot-candle (11 lux)	7 in (17.78 cm) Diameter	●

Light Source:	(3) UV-A LEDs, (1) white light LED
Lamp Style:	Pistol grip
Lamp Head Diameter:	3.3 in (8.38 cm)
Height:	7.5 in (19 cm)
Width:	3.5 in (8.9 cm)
Weight:	1.7 lb (0.73 kg) (without battery pack)
White Light LED Intensity:	400 foot-candles (4,306 lux)
Power Requirements:	100-120VAC / 12VDC (Also available in 230V & 240V versions)
Battery Pack:	Type: 12V, NiMH (rechargeable) Run time: 3.5 hours continuous Charge time: 2 hours

① UV-A intensity reading taken with the Spectroline® AccuMAX™ Series meter, and is factory set to the value shown.

\*Each lamp is fitted with an 8-foot cord and the appropriate plug for the country of destination. An optional 20-foot cord is available. The "/20" suffix denotes the 20-foot power cord options.






**uVision™ 365  
AC/DC MOBILE KIT**

**UV-365MEH**

**Kit Includes:**  
Lamp with AC power supply, UV-absorbing spectacles, battery pack with 12V rechargeable NiMH battery, comes in a padded case.

**CERTIFICATE OF  
LIGHT OUTPUT**

## UV-A Beam Profiles

