

- Best in class flow rates VPX7 10CFM, VP87 8CFM, and VP67 6CFM get the job done fast.
 All three pumps are lightweight & portable.
- Durable, sturdy pumps with a strong base and a small footprint eliminate spills. Easy to use hose valve ports keep hoses in line and easy to work around.
- RunQuick® Oil Change System allows oil changes on the fly – no need to turn off the pump and you won't lose vacuum.
- Massive back-lit oil reservoir with removable window for cleaning lets you clearly see the condition of the oil while the pump is running.





REVOLUTIONARY RUNQUICK® OIL CHANGE SYSTEM

Clean oil is key for an efficient evacuation and so easy to achieve with the RunQuick® Oil Change System. Monitor oil condition through a large backlit window that is removable for cleaning. Replace oil with the 8 ounce on-board spare in under 20 seconds, while the pump is running, without losing vacuum. Quick, clean, and easy.





| Flow Rate, Nominal | 10 CFM | 8 CFM | 6 CFM |
|------------------------------|---|---|---|
| Pump Body | EPO Coated aluminum alloy* | Cast iron | Cast iron |
| Motor | ¾ HP DC Motor | ¾ HP DC Motor | 1/2 HP AC Motor |
| Weight | 24lbs | 27lbs | 29lbs |
| Intake port | 4 in-line (1) 1/4", (2) 3/8", (1) 1/2" | 4 in-line (1) 1/4", (2) 3/8", (1) 1/2" | 4 in-line (1) 1/4", (2) 3/8", (1) 1/2" |
| RunQuick® Oil Change System | Two 8oz bottles of oil | Two 8oz bottles of oil | Two 8oz bottles of oil |
| Sturdy base, small footprint | 1346 cubic in 15 x 7.8 x 11.5 | 1346 cubic in 15 x 7.8 x 11.5 | 1346 cubic in 15 x 7.8 x 11.5 |
| Backlit oil reservoir | Yes | Yes | Yes |
| Gas ballast | Yes | Yes | Yes |
| Next Gen Refrigerants | A2L certified | A2L certified | A2L certified |