



## Superior AccuTrak® VPE-GN Gooseneck Find Leaks in Hard to Reach Places!



### The Patented Superior AccuTrak® VPE-GN State-of-the-Art Technology to Find and Locate Leaks

**AccuTrak®** is extremely sensitive to the ultrasonic sound of a turbulent gas leak.

Using a technology called “heterodyning” it translates the sound to a lower frequency which your ear can interpret. **AccuTrak®** maintains the original sound characteristics making it possible to distinguish leaks from other competing background sounds. **AccuTrak®** is so sensitive you can actually hear the blink of an eye, yet most background noise will not interfere with detection accuracy.

#### Capabilities:

- Works equally well for compressed Air or Nitrogen.
- Not affected by wind or high concentrations of leaked gas or refrigerant.
- Capable of detecting leaks equivalent to 1.5 oz/year of Refrigerant.
- Able to detect a 5 psi leak through a 0.005” (5/1000 inch) hole, from a 20-30 foot distance depending on background noise.
- Easily detects any gas that generates ultrasonic sound during flow including vacuum leaks.

#### Applications:

- Leak Detection: Air, Vacuum, Refrigerants, ANY GAS!
- Pinpoint Hard to Reach Refrigeration Leaks
- Test Window and Door Seals with Sound Generator
- Scan for Vacuum Leaks
- Hear Valve Stem and Tire Leaks

**The New 9½” Flexible Gooseneck Makes  
Leak Detection Easy in Hard-To-Reach Places!**



## VPE is offered in a Variety of Kits to meet the needs of any Professional!

### Features of the **AccuTrak® VPE-GN**:

- **Audio Output:** 0 Hz to 4 kHz Natural Sound conversion allows you to Hear the Leak, and distinguish leaks from mechanical or other background ultrasound.
- **Visual Output:** 10 element bar graph provides quick and intuitive visual indication to presence of and relative strength of ultrasound.
- **Adjustable Sensitivity:** allows operator to quickly identify leaks from a distance and then zero in on the exact location of the leak.



### VPE-GN Pro-Plus Kit Includes:

Model VPE-GN, Detector, Industrial Grade Noise Cancelling Head Set, Burst Tone Ultrasonic Sound Generator, Flexible Wave Guide, NEW Canvas Belt Pack, Hard Carrying Case with foam inserts, Alkaline Battery, User's Manual

### **AccuTrak® VPE-GN Specifications**

#### **Mechanical:**

Dimensions: (LWD) 4.15" (10.5cm) X 2.4" (61mm) X .875" (22.2mm)  
 Body Length: 4.15" (10.5 cm)  
 Goosneck Lgth: 9.5" (24.1cm)  
 Body Materials: ABS  
 Body Finish: Blue ABS  
 Connector: 3.5mm Stereo  
 Top Label: Velvet Lexan, Back Printed  
 Weight: 0.3lb (138gr) Includes Battery

#### **Electrical:**

Airborne Sensor Sensitivity:	-80db/V-μbar
Detection Performance:	1.5oz/yr Refrigerant
Ultrasound Converter type:	Heterodyne
Airborn Frequency response:	36kHz-42kHz
Heterodyne Oscillator:	Analog
Heterodyne Filter:	4kHz
Controls:	1 Button
Sensitivity Control:	Continually Variable Slide
Output, Audio:	0Hz to 4kHz
Output, Visual:	10 Element Bar Graph
Battery Type:	Std. 9 Volt Alkaline
Run Time:	80-120 hrs

### **AccuTrak® Burst Tone Sound Generator - an Essential Accessory**



The **AccuTrak®** Sound Generator when used together with **AccuTrak® VPE-GN** forms a non-invasive leak detection system capable of finding leaks in enclosures, including refrigerator/freezer door gaskets, truck or auto window seals, trunk gaskets, aircraft cabins, various tanks, vessels, or any other container that needs to be leak-free.

The **AccuTrak®** Sound Generator is used to "pressurize" rooms and enclosures with it's sound. This sound is above the human hearing range, and cannot be heard. It can penetrate through minute cracks, even ones that are not directly behind the leak point, and exit through it. The VPE-GN can trace the path air, or water, will take to cause a leak. The **AccuTrak® VPE-GN** receives the ultrasonic sound that escapes from the leak point, processes it and displays its strength. The bigger the leak is, the higher the volume in the headset. Burst Mode: If the back-

ground noise is extremely loud in a particular area, using Burst Tone will make the output of the sound generator much easier to identify.

### **AccuTrak® Sound Generator Specifications:**

Frequency Control - Precision Crystal Oscillator  
 Frequency Accuracy + /- 50 parts per million  
 Output Intensity - 115 db at 30cm. (nominal)  
 Battery Type - Std. 9 Volt Alkaline

Output Frequency - 40 kHz (+/- 2.5 Hz)  
 Precision Voltage Regulator - 1% Regulation  
 Dual Mode Output - Continuous or Burst Tone  
 Battery Life (approx.) - 70 hrs. Continuous, 90 hrs. Burst