



Series
WE02

3-Piece NPT Stainless Steel Ball Valve

Full Port, Vented Ball, Electric or Pneumatic Actuators

VALVES

Valves, Ball,
Automated



WE02-DHD00



WE02-DDA01



WE02-DDA01-AA04



WE02-DTD01-A



WE02-CTI01-A



Scan here
to watch
product video

The Series WE02 incorporates a full port 3-piece SS ball valve for great flow rates with minimal pressure drop. The valve features a blowout proof stem for added safety, reinforced PTFE seats and seals for longer life, and a 316 SS (ASTM CF8M) ball for better performance. Actuators are direct mounted creating a compact assembly for tight spaces. Limit switches are able to be mounted directly to the valves allowing for remote position indication.

The Series WE02 can be configured with either an electric or pneumatic actuator. Electric actuators are available in weatherproof or explosion-proof, a variety of supply voltages and two-position or modulating control. Two-position actuators use the supply voltage to drive the valve open or closed, while the modulating actuator accepts a 4 to 20 mA input for valve positioning. Actuators feature thermal overload protection and permanently lubricated gear train.

SPECIFICATIONS VALVE

Service: Compatible liquids and gases.

Body: 3-piece.

Line Sizes: 1/2 to 3" .

End Connections: Female NPT.

Pressure Limits: 28" Hg to 1000 psi (-0.7 to 69 bar) up to 250°F.

Wetted Materials:

Body and ball: 316 SS (CF8M);

Stem: 316 SS;

Seat: RTFE/PTFE;

Seal, Washer, and Packing: PTFE.

Temperature Limits: -20 to 392°F (-29 to 200°C).

Other Materials:

O-ring: Fluoroelastomer;

Handle: 304 SS;

Washer: 301 SS;

Stem Nut, Locking Device,

Gland Ring: 304 SS;

Handle Sleeve: PVC.

ACTUATORS

Pneumatic "DA" and "SR" Series

Type: DA series is double acting and SR series is spring return (rack and pinion).

Normal Supply Pressure:

DA: 40 to 115 psi (2.7 to 7.9 bar);

SR: 80 psi (5.5 bar).

Maximum Supply Pressure: 120 psi (8.6 bar).

Air Connections:

DA01: 1/8" female NPT;

DA02 to DA05: 1/4" female NPT;

SR02 to SR07: 1/4" female NPT.

Housing Material: Anodized aluminum body and epoxy coated aluminum end caps.

Temperature Limits: -40 to 176°F (-40 to 80°C).

Accessory Mounting: NAMUR standard.

The pneumatic double acting actuator uses an air supply to drive the valve open and closed. The actuator has two supply ports, with one driving the valve open and the other driving the valve closed. Spring return pneumatic actuators use the air supply to open the valve, and internally loaded springs return the valve to the closed position. Also available is the SN solenoid valve to electrically switch the air supply pressure between the air supply ports for opening and closing the valve. Actuators are constructed of anodized and epoxy coated aluminum for years of corrosion free service.

FEATURES

- Capable of being configured to fit any application
- Limit switches can be mounted to manual valves for remote monitoring

Electric "TD" and "MD" Series Power Requirements:

110 VAC, 220 VAC, 24 VAC or 24 VDC (MD models not available in 24 VDC).

Power Consumption: See instruction manual.

Cycle Time (per 90°):

TD01: 4 s;

MD01: 10 s;

TD02 and MD02: 20 s;

TD03 and MD03: 30 s.

Duty Rating: 85%.

Enclosure Rating: NEMA 4X (IP67).

Housing Material: Powder coated aluminum.

Temperature Limits: -22 to 140°F (-30 to 60°C).

Electrical Connection: 1/2" female NPT.

Modulating Input: 4 to 20 mA.

Standard Features: Manual override, position indicator, and TD models come with two limit switches.

Electric "TI" and "MI" Series

Power Requirements: 110 VAC, 220 VAC, 24 VAC or 24 VDC.

Power Consumption: See instruction manual.

Cycle Time (per 90°): See instruction manual.

Duty Rating: See instruction manual.

Enclosure Rating: NEMA 7, designed to meet hazardous locations: Class I, Group C & D; Class II, Group E, F & G; Division I & II.

Housing Material: Powder coated aluminum.

Temperature Limits: -40 to 140°F (-40 to 60°C).

Electrical Connection: 1/2" female NPT.

Modulating Input: 4 to 20 mA.

Standard Features: Position indicator and two limit switches.

Popular Models

	Cv (gal/min)	Hand Operated Model	Double Acting Pneumatic Model	Spring Return Pneumatic Model	NEMA 4X Two- Position Electric (110 VAC) Model	NEMA 4X Modulating Electric (110 VAC) Model
1/2"	36.64	WE02-CHD00	WE02-CDA01	WE02-CSR02	WE02-CTD01-A	WE02-CMD01-A
3/4"	67.69	WE02-DHD00	WE02-DDA01	WE02-DSR02	WE02-DTD01-A	WE02-DMD01-A
1"	110.27	WE02-EHD00	WE02-EDA02	WE02-ESR03	WE02-ETD01-A	WE02-EMD01-A
1-1/4"	184.73	WE02-FHD00	WE02-FDA02	WE02-FSR03	WE02-FTD01-A	WE02-FMD01-A
1-1/2"	266.62	WE02-GHD00	WE02-GDA03	WE02-GSR04	WE02-GTD02-A	WE02-GMD01-A
2"	485.3	WE02-HHD00	WE02-HDA03	WE02-HSR05	WE02-HTD02-A	WE02-HMD02-A
2-1/2"	791.57	WE02-IHD00	WE02-IDA04	WE02-ISR07	WE02-ITD03-A	WE02-IMD03-A
3"	1151.95	WE02-JHD00	WE02-JDA05	WE02-JSR07	WE02-JTD03-A	WE02-JMD03-A

WE02 Hand Operated and Pneumatic Actuator Model Chart

Example	WE02	CSR02	N	N	09		WE02-CSR02-NN09
Series	WE02						316SS 3-Piece NPT
Size and Actuators		CHD00 DHD00 EHD00 FHD00 GHD00 HHD00 IHD00 JHD00 CDA01 DDA01 EDA02 FDA02 GDA03 HDA03 IDA04 JDA05 CSR02 DSR02 ESR03 FSR03 GSR04 HSR05 ISR07 JSR07					1/2" Hand Operated 3/4" Hand Operated 1" Hand Operated 1-1/4" Hand Operated 1-1/2" Hand Operated 2" Hand Operated 2-1/2" Hand Operated 3" Hand Operated 1/2" Double Acting 3/4" Double Acting 1" Double Acting 1-1/4" Double Acting 1-1/2" Double Acting 2" Double Acting 2-1/2" Double Acting 3" Double Acting 1/2" Spring Return 3/4" Spring Return 1" Spring Return 1-1/4" Spring Return 1-1/2" Spring Return 2" Spring Return 2-1/2" Spring Return 3" Spring Return
Solenoid			N A				No Solenoid NEMA 4X NAMUR Solenoid
Solenoid Voltage				N A B C D E			No Solenoid 110 VAC 220 VAC 24 VAC 24 VDC 12 VDC
Positioner and Switches					00 01 02 03 04 05 06 07 08 09		None 42AD0 Exp Limit Switch 45VD0 Exp Position Transmitter 42AD0-B ATEX Limit Switch 42AD0-IE IECEx Limit Switch VPI-M01 NEMA 4X Limit Switch QV-210101 Poly Limit Switch VPS and P1 Prox Switch 265ER-D5 Positioner 285ER-D5 Smart Positioner
Options						NO	Fail Open Spring Return Actuator

WE02 Electric Actuator Model Chart

Example	WE02	ETD01	B	WE02-ETD01-B
Series	WE02			316SS 3-Piece NPT
Size and Actuators		CTD01 DTD01 ETD01 FTD01 GTD02 HTD02 ITD03 JTD03 CMD01 DMD01 EMD01 FMD01 GMD01 HMD02 IMD03 JMD03 CTI01 DTI01 ETI02 FTI02 GTI03 HTI04 ITI05 JTI05 CMI01 DMI01 EMI02 FMI02 GMI03 HMI04 IMI05 JMI05		1/2" NEMA 4X Two-Position 3/4" NEMA 4X Two-Position 1" NEMA 4X Two-Position 1-1/4" NEMA 4X Two-Position 1-1/2" NEMA 4X Two-Position 2" NEMA 4X Two-Position 2-1/2" NEMA 4X Two-Position 3" NEMA 4X Two-Position 1/2" NEMA 4X Modulating 3/4" NEMA 4X Modulating 1" NEMA 4X Modulating 1-1/4" NEMA 4X Modulating 1-1/2" NEMA 4X Modulating 2" NEMA 4X Modulating 2-1/2" NEMA 4X Modulating 3" NEMA 4X Modulating 1/2" Exp Two-Position 3/4" Exp Two-Position 1" Exp Two-Position 1-1/4" Exp Two-Position 1-1/2" Exp Two-Position 2" Exp Two-Position 2-1/2" Exp Two-Position 3" Exp Two-Position 1/2" Exp Electric Modulating 3/4" Exp Electric Modulating 1" Exp Electric Modulating 1-1/4" Exp Electric Modulating 1-1/2" Exp Electric Modulating 2" Exp Electric Modulating 2-1/2" Exp Electric Modulating 3" Exp Electric Modulating
Actuator Voltage			A B C D	110 VAC 220 VAC 24 VAC 24 VDC

VALVES

Valves, Ball,
Automated

ACCESSORIES

R2-2120, Air Regulator

AFR2-2, Instrument Air Filter Regulator

VB-01, Volume Booster